

屋内照明器具特性

品番 (品名)	T 3 A M 4 0 0 1 2									
光源	LED4000_90_2960 x1 2960.0 1 m									
管理番号	K0193158 (0) D 1									
B Z 分類	B Z 5 / 0.7 / B Z 4									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %			
	上方光束		0 %	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
	下方光束		100 %		床	10 %				10 %				10 %				10 %				0 %
室指数	照明率 (X 0.01)																			Z C M		
保守率	良	0.88	0.6	5.8	4.6	3.8	3.3	5.7	4.5	3.8	3.3	5.4	4.4	3.8	3.3	5.2	4.3	3.7	3.3	3.1		
	中	0.86	0.8	6.8	5.7	4.9	4.4	6.7	5.6	4.9	4.4	6.4	5.5	4.8	4.3	6.2	5.4	4.8	4.3	4.1		
	否	0.81	1.0	7.5	6.4	5.7	5.1	7.3	6.4	5.6	5.1	7.0	6.2	5.6	5.1	6.8	6.0	5.5	5.0	4.8		
			1.25	8.1	7.1	6.4	5.9	7.9	7.0	6.4	5.9	7.6	6.9	6.3	5.8	7.3	6.7	6.2	5.8	5.5		
下方投影面積			c m ²		1.5	8.5	7.6	7.0	6.4	8.3	7.5	6.9	6.4	8.0	7.3	6.8	6.4	7.7	7.2	6.7	6.3	6.1
			c m ²		2.0	9.0	8.3	7.8	7.3	8.9	8.2	7.7	7.2	8.6	8.0	7.6	7.2	8.3	7.8	7.4	7.1	6.8
取付高さ	器具間隔最大限				2.5	9.4	8.8	8.3	7.8	9.2	8.7	8.2	7.8	8.9	8.5	8.1	7.7	8.7	8.3	7.9	7.6	7.4
	横方向 (A)	縦方向 (B)			3.0	9.6	9.1	8.6	8.3	9.5	9.0	8.6	8.2	9.2	8.8	8.4	8.1	8.9	8.6	8.3	8.0	7.7
1.5m	1.84 m	1.88 m			4.0	9.9	9.5	9.1	8.8	9.8	9.4	9.1	8.8	9.5	9.2	8.9	8.6	9.2	9.0	8.7	8.5	8.2
2	2.45	2.48			5.0	10.1	9.8	9.5	9.2	10.0	9.6	9.4	9.1	9.7	9.4	9.2	9.0	9.4	9.2	9.0	8.8	8.6
2.5	3.07	3.08			7.0	10.3	10.1	9.8	9.6	10.2	9.9	9.7	9.5	9.9	9.7	9.5	9.4	9.7	9.5	9.4	9.2	8.9
3	3.66	3.67			10.0	10.5	10.3	10.1	10.0	10.3	10.2	10.0	9.9	10.1	9.9	9.8	9.7	9.8	9.7	9.6	9.5	9.2

