

屋内照明器具特性

品番 (品名)	XAS7311L				
光源	LED2700_70_790	x1	790.0	lm	
管理番号	K0171367(0)D 1				
BZ分類	BZ3/2.8/BZ2/4.5/BZ3/6.0/BZ2				

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 42%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	58%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.67	0.6	5.5	4.4	3.7	3.3	5.1	4.2	3.6	3.2	4.5	3.8	3.3	2.9	4.0	3.4	3.0	2.7	2.2
	中	0.63	0.8	6.4	5.4	4.8	4.3	6.0	5.2	4.6	4.1	5.3	4.6	4.2	3.8	4.7	4.1	3.8	3.5	2.9
	否	0.56	1.0	7.0	6.1	5.5	5.0	6.6	5.8	5.3	4.8	5.8	5.2	4.8	4.4	5.1	4.7	4.3	4.0	3.4
			1.25	7.6	6.8	6.2	5.7	7.1	6.4	5.9	5.5	6.3	5.8	5.3	5.0	5.5	5.1	4.8	4.5	3.8
下方投影面積	cm ²		1.5	7.9	7.2	6.7	6.2	7.5	6.9	6.4	6.0	6.6	6.1	5.7	5.4	5.8	5.4	5.1	4.9	4.1
等価発光面積	cm ²		2.0	8.4	7.8	7.4	7.0	7.9	7.4	7.0	6.7	7.0	6.6	6.3	6.0	6.1	5.9	5.6	5.4	4.5
取付高さ	器具間隔最大限		2.5	8.7	8.2	7.8	7.5	8.2	7.8	7.4	7.1	7.2	6.9	6.7	6.4	6.3	6.1	5.9	5.7	4.7
	横方向 (A)	縦方向 (B)	3.0	8.9	8.5	8.1	7.8	8.4	8.0	7.7	7.4	7.4	7.1	6.9	6.7	6.5	6.3	6.1	6.0	4.9
H _m	1.22H _m	1.22H _m	4.0	9.2	8.8	8.5	8.3	8.6	8.3	8.1	7.9	7.6	7.4	7.2	7.0	6.7	6.5	6.4	6.3	5.1
			5.0	9.3	9.0	8.8	8.6	8.8	8.5	8.3	8.1	7.8	7.6	7.4	7.3	6.8	6.7	6.6	6.4	5.2
			7.0	9.5	9.3	9.1	8.9	8.9	8.8	8.6	8.5	7.9	7.8	7.7	7.5	6.9	6.8	6.7	6.7	5.4
			10.0	9.6	9.5	9.3	9.2	9.1	8.9	8.8	8.7	8.0	7.9	7.8	7.8	7.0	7.0	6.9	6.8	5.5

