

屋内照明器具特性

品番 (品名)	LGB15116	
光源	LLD2000LCT1 ×1	531.0 lm
管理番号	K0190525(0)DR1	
BZ分類	BZ3	

器具効率	71%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		71%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.67	0.6	4.6	3.9	3.5	3.1	4.6	3.9	3.4	3.1	4.4	3.8	3.4	3.1	4.3	3.8	3.4	3.1	3.0	
	中	0.63	0.8	5.3	4.6	4.1	3.8	5.2	4.5	4.1	3.8	5.0	4.5	4.1	3.8	4.8	4.4	4.0	3.8	3.6	
	否	0.56	1.0	5.7	5.0	4.6	4.3	5.6	5.0	4.6	4.2	5.4	4.9	4.5	4.2	5.2	4.8	4.5	4.2	4.1	
			1.25	6.0	5.4	5.0	4.7	5.9	5.4	5.0	4.7	5.7	5.3	4.9	4.6	5.5	5.2	4.9	4.6	4.5	
下方投影面積	cm ²		1.5	6.2	5.7	5.3	5.0	6.1	5.7	5.3	5.0	5.9	5.5	5.2	5.0	5.8	5.4	5.2	4.9	4.8	
等価発光面積	cm ²		2.0	6.6	6.1	5.8	5.5	6.5	6.1	5.8	5.5	6.3	5.9	5.7	5.4	6.1	5.8	5.6	5.4	5.2	
取付高さ	器具間隔最大限		2.5	6.8	6.4	6.1	5.8	6.7	6.3	6.1	5.8	6.5	6.2	6.0	5.7	6.3	6.1	5.9	5.7	5.5	
	横方向 (A)	縦方向 (B)	3.0	6.9	6.6	6.3	6.1	6.8	6.5	6.3	6.1	6.6	6.4	6.2	6.0	6.4	6.2	6.1	5.9	5.7	
Hm	1.32Hm	1.32Hm	4.0	7.1	6.8	6.6	6.4	7.0	6.8	6.6	6.4	6.8	6.6	6.4	6.3	6.6	6.5	6.3	6.2	6.0	
			5.0	7.2	7.0	6.8	6.6	7.1	6.9	6.7	6.6	6.9	6.8	6.6	6.5	6.7	6.6	6.5	6.4	6.2	
			7.0	7.3	7.2	7.0	6.9	7.2	7.1	7.0	6.8	7.0	6.9	6.8	6.7	6.9	6.8	6.7	6.6	6.4	
			10.0	7.4	7.3	7.2	7.1	7.3	7.2	7.1	7.0	7.1	7.1	7.0	6.9	7.0	6.9	6.8	6.8	6.6	

