

屋内照明器具特性

品番 (品名)	XDL413PGN(JYOUJI)											
光源	LED5000_85_1940 x1 1940.0lm											
管理番号	K0194635(0)D1											
BZ分類	BZ5/1.4/BZ4											

器具効率	100%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率																		
下方光束	100%	壁																		
		床																		
		室指数	照明率 (X0.01) ZCM																	
保守率	良	0.81	0.6	5.7	4.5	3.7	3.2	5.6	4.5	3.7	3.2	5.4	4.3	3.7	3.2	5.1	4.2	3.6	3.2	3.0
	中	0.77	0.8	6.7	5.6	4.8	4.3	6.6	5.5	4.8	4.2	6.3	5.4	4.7	4.2	6.1	5.3	4.7	4.2	4.0
	否	0.68	1.0	7.4	6.3	5.6	5.0	7.2	6.3	5.5	5.0	7.0	6.1	5.5	5.0	6.7	6.0	5.4	4.9	4.7
			1.25	8.0	7.1	6.3	5.8	7.8	7.0	6.3	5.8	7.5	6.8	6.2	5.7	7.3	6.6	6.1	5.7	5.4
下方投影面積			1.5	8.4	7.6	6.9	6.3	8.3	7.5	6.8	6.3	8.0	7.3	6.7	6.3	7.7	7.1	6.6	6.2	6.0
			2.0	9.0	8.3	7.7	7.2	8.8	8.2	7.6	7.2	8.5	8.0	7.5	7.1	8.2	7.8	7.4	7.0	6.8
等価発光面積			2.5	9.3	8.7	8.2	7.8	9.2	8.6	8.1	7.7	8.9	8.4	8.0	7.6	8.6	8.2	7.9	7.5	7.3
	取付高さ	器具間隔最大限	3.0	9.6	9.1	8.6	8.2	9.4	8.9	8.5	8.1	9.1	8.7	8.4	8.0	8.9	8.5	8.2	7.9	7.7
	横方向 (A)	縦方向 (B)	4.0	9.9	9.5	9.1	8.8	9.7	9.4	9.0	8.7	9.5	9.1	8.9	8.6	9.2	8.9	8.7	8.5	8.2
1.5m	1.93m	2.11m	5.0	10.1	9.7	9.4	9.1	9.9	9.6	9.3	9.1	9.7	9.4	9.2	8.9	9.4	9.2	9.0	8.8	8.5
2	2.55	2.65	7.0	10.3	10.0	9.8	9.6	10.2	9.9	9.7	9.5	9.9	9.7	9.5	9.3	9.7	9.5	9.3	9.2	8.9
2.5	3.17	3.21	10.0	10.5	10.3	10.1	9.9	10.3	10.2	10.0	9.8	10.1	9.9	9.8	9.7	9.8	9.7	9.6	9.5	9.2
3	3.78	3.79																		

