

# 屋内照明器具特性

品番 (品名)	XDL442PGN(JYOUJI)										
光源	LED5000_85_3880 x1 3880.0 lm										
管理番号	K0194635(0)D 1										
BZ分類	BZ5/1.4/BZ4										

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%			
上方光束	0%	室指数	照明率 ( X0.01)																ZCM	
下方光束	100%																			
保守率	良 中 否	0.81	0.6	5.7	4.5	3.7	3.2	5.6	4.5	3.7	3.2	5.4	4.3	3.7	3.2	5.1	4.2	3.6	3.2	3.0
		0.77	0.8	6.7	5.6	4.8	4.3	6.6	5.5	4.8	4.2	6.3	5.4	4.7	4.2	6.1	5.3	4.7	4.2	4.0
		0.68	1.0	7.4	6.3	5.6	5.0	7.2	6.3	5.5	5.0	7.0	6.1	5.5	5.0	6.7	6.0	5.4	4.9	4.7
			1.25	8.0	7.1	6.3	5.8	7.8	7.0	6.3	5.8	7.5	6.8	6.2	5.7	7.3	6.6	6.1	5.7	5.4
下方投影面積	c m <sup>2</sup>	1.5	8.4	7.6	6.9	6.3	8.3	7.5	6.8	6.3	8.0	7.3	6.7	6.3	7.7	7.1	6.6	6.2	6.0	
		2.0	9.0	8.3	7.7	7.2	8.8	8.2	7.6	7.2	8.5	8.0	7.5	7.1	8.2	7.8	7.4	7.0	6.8	
取付高さ	器具間隔最大限		2.5	9.3	8.7	8.2	7.8	9.2	8.6	8.1	7.7	8.9	8.4	8.0	7.6	8.6	8.2	7.9	7.5	7.3
	横方向 (A)	縦方向 (B)	3.0	9.6	9.1	8.6	8.2	9.4	8.9	8.5	8.1	9.1	8.7	8.4	8.0	8.9	8.5	8.2	7.9	7.7
1.5m	1.93m	2.11m	4.0	9.9	9.5	9.1	8.8	9.7	9.4	9.0	8.7	9.5	9.1	8.9	8.6	9.2	8.9	8.7	8.5	8.2
2	2.55	2.65	5.0	10.1	9.7	9.4	9.1	9.9	9.6	9.3	9.1	9.7	9.4	9.2	8.9	9.4	9.2	9.0	8.8	8.5
2.5	3.17	3.21	7.0	10.3	10.0	9.8	9.6	10.2	9.9	9.7	9.5	9.9	9.7	9.5	9.3	9.7	9.5	9.3	9.2	8.9
3	3.78	3.79	10.0	10.5	10.3	10.1	9.9	10.3	10.2	10.0	9.8	10.1	9.9	9.8	9.7	9.8	9.7	9.6	9.5	9.2

