

屋内照明器具特性	
品番 (品名)	S L B 1 6 7 8 6
光源	LED2700_70_379 ×1 379.0 l m
管理番号	K0146455 (0) DB 1
B Z 分類	B Z 6

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		15 %	室指数	照明率 (X0.01)																			Z	C	M
下方光束		85 %																							
保守率		良	0.63	0.6	51	39	30	25	49	37	30	24	45	35	28	23	42	33	27	22	19				
		中	0.6	0.8	61	48	40	34	58	47	39	33	54	44	37	32	49	41	35	30	27				
		否	0.56	1.0	67	55	47	41	64	54	46	40	59	50	43	38	55	47	41	37	33				
				1.25	73	62	54	48	70	60	53	47	65	56	50	45	60	53	47	43	38				
下方投影面積		cm ²		1.5	77	67	59	53	74	65	58	52	69	61	55	50	64	57	52	48	43				
等価発光面積		cm ²		2.0	83	74	67	62	80	72	66	60	74	68	62	57	69	63	59	55	50				
取付高さ	器具間隔最大限			2.5	87	79	73	67	84	77	71	66	78	72	67	63	72	68	64	60	54				
	横方向 (A)		縦方向 (B)	3.0	89	83	77	72	86	80	75	70	80	75	71	67	75	71	67	64	58				
H m	0.52 H m	0.54 H m	4.0	93	87	82	78	90	85	80	76	84	80	76	72	78	75	72	69	63					
			5.0	95	90	86	82	92	87	84	80	86	82	79	76	80	78	75	72	66					
			7.0	97	94	90	87	94	91	88	85	89	86	83	81	83	81	79	77	70					
			10.0	99	97	94	92	96	94	92	89	91	89	87	85	85	84	82	81	74					

