

# 屋内照明器具特性

品番 (品名)	SLB16789									
光源	LED2700_70_341 x1					341.0 lm				
管理番号	K0146454(0)DB1									
BZ分類	BZ5/2.8/BZ6									

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		13%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		87%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																			ZCM	
保守率	良	0.63	0.6	0.6	53	41	33	28	52	40	33	27	48	38	31	26	45	36	30	26	23
	中	0.6	0.6	0.6	63	51	43	37	60	49	42	36	56	47	40	35	52	44	38	34	31
	否	0.56	0.56	0.56	69	58	50	44	66	56	49	43	62	53	46	41	58	50	44	40	36
					75	64	56	50	72	62	55	49	67	59	53	48	62	56	50	46	42
下方投影面積			c m <sup>2</sup>	1.5	79	69	61	55	76	67	60	54	71	63	57	52	66	60	55	50	46
	等価発光面積		c m <sup>2</sup>	2.0	84	76	69	63	81	74	67	62	76	70	64	60	71	66	61	57	53
取付高さ	器具間隔最大限			2.5	88	80	74	69	85	78	72	68	79	74	69	65	74	70	66	62	57
	横方向 (A)	縦方向 (B)		3.0	90	84	78	73	87	81	76	72	82	77	73	69	77	73	69	66	61
H m	0.87 H m	0.92 H m		4.0	93	88	83	79	91	86	81	77	85	81	77	74	80	77	74	71	65
				5.0	96	91	87	83	93	89	85	81	87	84	81	78	82	79	77	74	69
				7.0	98	94	91	88	95	92	89	86	90	87	85	82	85	83	81	79	73
				10.0	100	97	95	92	97	95	93	90	92	90	88	86	87	85	84	82	76

