

屋内照明器具特性	
品番 (品名)	S L B 1 9 4 1 1 W
光源	L D A 7 L - D - G / S / Z 6 × 4 8 1 0 . 0 l m
管理番号	K 0 1 4 0 2 7 0 (0) D B 1
B Z 分類	B Z 8

器具効率		8 9 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束		4 0 %	室指数	照明率 (X 0 . 0 1)																	Z C M
下方光束		4 9 %																			
保守率		良	0 . 6 3	0 . 6	4 1	3 0	2 2	1 8	3 7	2 7	2 1	1 6	3 1	2 3	1 8	1 4	2 6	2 0	1 5	1 2	8
		中	0 . 6	0 . 8	4 8	3 7	3 0	2 4	4 4	3 4	2 8	2 3	3 7	2 9	2 4	2 0	3 1	2 4	2 0	1 7	1 1
		否	0 . 5 6	1 . 0	5 3	4 3	3 5	2 9	4 9	4 0	3 3	2 8	4 1	3 4	2 8	2 4	3 4	2 8	2 4	2 0	1 4
				1 . 2 5	5 8	4 8	4 1	3 5	5 4	4 5	3 8	3 3	4 5	3 8	3 3	2 8	3 7	3 2	2 7	2 4	1 6
下方投影面積		c m ²		1 . 5	6 2	5 2	4 5	3 9	5 7	4 9	4 2	3 7	4 8	4 1	3 6	3 2	4 0	3 5	3 0	2 7	1 9
等価発光面積		c m ²		2 . 0	6 7	5 8	5 2	4 6	6 2	5 4	4 8	4 3	5 2	4 6	4 2	3 8	4 3	3 9	3 5	3 2	2 3
取付高さ	器具間隔最大限			2 . 5	7 0	6 3	5 7	5 1	6 5	5 8	5 3	4 8	5 5	5 0	4 5	4 2	4 6	4 2	3 8	3 5	2 5
	横方向 (A)		縦方向 (B)	3 . 0	7 2	6 6	6 0	5 5	6 7	6 1	5 6	5 2	5 7	5 2	4 8	4 5	4 8	4 4	4 1	3 8	2 8
H m	1 . 4 6 H m	1 . 4 2 H m	4 . 0	7 5	7 0	6 5	6 1	7 0	6 5	6 1	5 7	6 0	5 6	5 3	4 9	5 0	4 7	4 5	4 2	3 1	
			5 . 0	7 7	7 3	6 8	6 5	7 2	6 8	6 4	6 1	6 2	5 8	5 5	5 3	5 2	5 0	4 7	4 5	3 3	
			7 . 0	8 0	7 6	7 3	7 0	7 4	7 1	6 8	6 5	6 4	6 2	5 9	5 7	5 4	5 2	5 0	4 9	3 6	
			1 0 . 0	8 2	7 9	7 6	7 4	7 6	7 4	7 1	6 9	6 6	6 4	6 2	6 0	5 6	5 5	5 3	5 2	3 9	

