

屋内照明器具特性	
品番 (品名)	S L B 8 0 5 5 0
光源	LED3500_70_300 ×1 300.0 l m
管理番号	K0147441 (0) DB 1
B Z 分類	B Z 2

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束		5 0 %	室指数	照明率 (X 0 . 0 1) Z C M																	
下方光束		5 0 %																			
保守率		良 中 否	0 . 6 3	0 . 6	5 6	4 6	4 0	3 6	5 2	4 4	3 8	3 4	4 6	3 9	3 5	3 1	3 9	3 4	3 1	2 9	2 4
			0 . 6	0 . 8	6 4	5 5	4 9	4 4	6 0	5 2	4 7	4 2	5 2	4 6	4 2	3 9	4 5	4 0	3 7	3 5	2 8
			0 . 5 6	1 . 0	7 0	6 2	5 5	5 1	6 5	5 8	5 3	4 8	5 6	5 1	4 7	4 4	4 8	4 4	4 1	3 9	3 2
				1 . 2 5	7 5	6 7	6 1	5 7	7 0	6 3	5 8	5 4	6 0	5 5	5 2	4 9	5 1	4 8	4 5	4 3	3 4
下方投影面積		c m ²		1 . 5	7 8	7 1	6 6	6 2	7 3	6 7	6 2	5 8	6 3	5 9	5 5	5 2	5 4	5 1	4 8	4 6	3 6
			等価発光面積	c m ²	2 . 0	8 3	7 7	7 2	6 8	7 7	7 2	6 8	6 5	6 6	6 3	6 0	5 7	5 7	5 4	5 2	5 0
取付高さ	器具間隔最大限			2 . 5	8 6	8 1	7 6	7 3	8 0	7 6	7 2	6 9	6 9	6 6	6 3	6 1	5 8	5 6	5 4	5 3	4 1
	横方向 (A) 縦方向 (B)			3 . 0	8 7	8 3	8 0	7 6	8 2	7 8	7 5	7 2	7 0	6 8	6 5	6 3	6 0	5 8	5 6	5 5	4 2
H m	0 . 8 2 H m	1 . 4 1 H m		4 . 0	9 0	8 7	8 4	8 1	8 4	8 1	7 8	7 6	7 2	7 0	6 8	6 7	6 1	6 0	5 9	5 7	4 4
				5 . 0	9 1	8 9	8 6	8 4	8 5	8 3	8 1	7 9	7 3	7 2	7 0	6 9	6 2	6 1	6 0	5 9	4 5
				7 . 0	9 3	9 1	8 9	8 7	8 7	8 5	8 3	8 2	7 5	7 4	7 2	7 1	6 4	6 3	6 2	6 1	4 6
				1 0 . 0	9 4	9 3	9 1	9 0	8 8	8 7	8 6	8 4	7 6	7 5	7 4	7 3	6 4	6 4	6 3	6 3	4 7

