

屋内照明器具特性	
品番 (品名)	S L B 8 1 8 7 4
光源	LED2700_70_2215 x1 2215.0 1 m
管理番号	K0192584 (0) DR 1
B Z 分類	BZ8 / 0.7 / BZ7

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	32 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	68 %	室指数	照明率 (X0.01)																				Z C M
保守率	良	0.67	0.6	47	34	26	20	44	32	25	19	38	29	22	17	33	25	20	16	12			
	中	0.63	0.8	56	43	34	28	52	41	33	27	46	36	29	24	39	32	26	22	17			
	否	0.56	1.0	62	50	41	34	58	47	39	33	51	42	35	30	44	37	31	27	21			
			1.25	67	56	47	41	63	53	45	39	55	47	40	35	48	41	36	32	25			
下方投影面積		cm ²	1.5	72	61	53	46	67	58	50	44	59	51	45	40	51	45	40	36	28			
等価発光面積		cm ²	2.0	77	68	60	54	73	64	57	52	64	57	51	47	56	50	46	42	33			
取付高さ	器具間隔最大限		2.5	81	73	66	60	76	69	62	57	67	61	56	52	59	54	50	46	37			
	横方向 (A)	縦方向 (B)	3.0	84	76	70	64	79	72	66	61	70	65	60	56	61	57	53	50	40			
1.5m	2.06 m	2.15 m	4.0	87	81	76	71	83	77	72	67	73	69	65	61	65	61	58	55	45			
2	2.72	2.71	5.0	90	84	80	75	85	80	76	72	76	72	68	65	67	64	61	58	48			
2.5	3.38	3.3	7.0	92	88	84	81	88	84	80	77	78	75	73	70	70	67	65	63	52			
3	4.04	3.89	10.0	95	92	88	86	90	87	84	82	81	78	76	74	72	70	68	67	55			

