

# 屋内照明器具特性

品番 (品名)	SLB81883															
光源	LED3500_70_1210 x1 1210.0 1m															
管理番号	K0192613(0)DR1															
BZ分類	BZ8/0.7/BZ7															

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		32%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		68%		10%				10%				10%				10%				0%
室指数	照明率 ( X0.01 ) ZCM																				
保守率	良	0.67	0.6	47	34	26	20	44	32	25	19	38	29	22	17	33	25	20	16	11	
	中	0.63	0.8	56	43	34	28	52	41	33	27	45	36	29	24	39	32	26	22	17	
	否	0.56	1.0	62	50	41	34	58	47	39	33	50	41	35	30	44	36	31	26	20	
			1.25	67	56	47	41	63	53	45	39	55	47	40	35	48	41	36	31	25	
下方投影面積			1.5	71	61	53	46	67	57	50	44	59	51	45	40	51	45	40	35	28	
			2.0	77	68	60	54	73	64	57	51	64	57	51	46	56	50	46	42	33	
取付高さ	器具間隔最大限		2.5	81	73	66	60	76	69	62	57	67	61	56	51	59	54	50	46	37	
	横方向 (A)	縦方向 (B)	3.0	84	76	70	64	79	72	66	61	70	64	60	55	61	57	53	50	40	
1.5m	2.02m	1.93m	4.0	87	81	76	71	82	77	72	67	73	69	65	61	64	61	58	55	44	
2	2.69	2.54	5.0	89	84	79	75	85	80	75	72	75	72	68	65	67	64	61	58	48	
2.5	3.36	3.16	7.0	92	88	84	81	87	84	80	77	78	75	72	70	69	67	65	62	52	
3	4.01	3.78	10.0	95	91	88	86	90	87	84	82	81	78	76	74	72	70	68	66	55	

