

屋内照明器具特性

品番 (品名)	XED1231N																		
光源	LED5000_70_320 ×1 320.0 1m																		
管理番号	K0166789 (1) DB1																		
BZ分類	BZ1																		

器具効率	100%	天井	80%				70%				50%				30%				0%								
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%								
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%							
下方光束	100%		床	10%				10%				10%				10%				0%							
室指数	照明率 (X0.01) ZCM																										
保守率	良	0.63	0.6	0.56	0.6	82	76	72	69	82	76	72	69	80	75	72	69	79	74	71	69	68					
	中	0.6	0.6	0.6	0.8	89	83	79	76	88	83	79	76	86	82	78	76	85	81	78	76	74					
	否	0.56	0.56	0.56	1.0	93	87	84	81	92	87	83	81	90	86	83	80	88	85	82	80	79					
下方投影面積	cm ²	1.25	1.5	2.0	2.5	96	91	88	85	95	91	87	85	93	89	87	85	91	88	86	84	83					
		等価発光面積	cm ²	1.5	2.0	2.5	98	94	91	88	97	93	90	88	95	92	89	87	93	91	89	87	85				
取付高さ	器具間隔最大限		H _m	0.41H _m	0.41H _m	3.0	4.0	5.0	7.0	10.0	102	99	97	95	101	99	96	95	99	97	95	94	97	95	94	93	91
	横方向 (A)	縦方向 (B)				3.0	4.0	5.0	7.0	10.0	103	101	99	97	102	100	98	96	100	98	97	95	98	97	95	94	92
						4.0	5.0	7.0	10.0	104	103	101	100	103	102	100	99	101	100	99	97	99	98	97	96	94	
						5.0	7.0	10.0	105	104	102	101	100	104	103	102	100	101	100	99	100	99	98	97	96	95	
						7.0	10.0	106	105	104	103	101	100	104	103	102	101	100	101	100	99	99	98	97	96	95	
						10.0	107	106	105	105	106	105	104	104	103	103	102	102	101	101	100	100	99	97	96	95	

