

屋内照明器具特性

品番 (品名)	XED3 1 2 0 V	
光源	LED3500_70_500 ×1	500.0 l m
管理番号	K0166783 (1) DB 1	
BZ分類	BZ1	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %						
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %						
上方光束	0 %	反射率	壁	10 %				10 %				10 %				10 %				0 %					
下方光束	100 %		床	10 %				10 %				10 %				10 %				0 %					
		室指数	照明率 (X0.01)																ZCM						
保守率	良	0.63	0.6	0.56	0.6	82	76	72	69	82	76	72	69	80	75	71	69	79	74	71	69	68			
	中	0.6	0.6	0.6	0.8	89	83	79	76	88	83	79	76	86	82	78	76	85	81	78	76	74			
	否	0.56	0.56	0.56	1.0	92	87	84	81	92	87	83	81	90	86	83	80	88	85	82	80	79			
下方投影面積 等価発光面積	c m ²	1.25	1.5	2.0	1.25	96	91	88	85	95	91	87	85	93	89	87	84	91	88	86	84	83			
		2.0	2.5	3.0	2.0	100	97	95	92	99	96	94	92	97	95	93	91	96	94	92	90	89			
		3.0	4.0	5.0	3.0	102	99	97	95	101	99	96	95	99	97	95	94	97	95	94	93	91			
取付高さ	器具間隔最大限		H m	0.41 H m	0.41 H m	4.0	5.0	7.0	10.0	4.0	5.0	7.0	10.0	4.0	5.0	7.0	10.0	4.0	5.0	7.0	10.0	4.0	5.0	7.0	10.0
	横方向 (A)	縦方向 (B)				4.0	5.0	7.0	10.0	4.0	5.0	7.0	10.0	4.0	5.0	7.0	10.0	4.0	5.0	7.0	10.0	4.0	5.0	7.0	10.0

