

| 屋内照明器具特性 |                             |
|----------|-----------------------------|
| 品番 (品名)  | S L B 8 0 5 8 1             |
| 光源       | LED2700_70_130 ×1 130.0 l m |
| 管理番号     | K0147468 ( 0 ) DB 1         |
| B Z 分類   | BZ5 / 0.7 / BZ6             |

| 器具効率     |           | 100 %           | 反射率             | 天井            | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |  |   |    |
|----------|-----------|-----------------|-----------------|---------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|--|---|----|
|          |           |                 |                 | 壁             | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |  |   |    |
|          |           |                 |                 | 床             | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |  |   |    |
| 上方光束     |           | 50 %            | 室指数             | 照明率 ( X0.01 ) |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |  | Z | CM |
| 下方光束     |           | 50 %            |                 |               |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |  |   |    |
| 保守率      |           | 良<br>中<br>否     | 0.63            | 0.6           | 49   | 38 | 30 | 25 | 45   | 35 | 28 | 24 | 38   | 30 | 25 | 21 | 32   | 25 | 21 | 18 | 13  |  |   |    |
|          |           |                 | 0.6             | 0.8           | 57   | 46 | 38 | 33 | 53   | 43 | 36 | 31 | 44   | 37 | 31 | 27 | 36   | 31 | 26 | 23 | 17  |  |   |    |
|          |           |                 |                 | 1.0           | 63   | 52 | 45 | 39 | 58   | 48 | 42 | 36 | 48   | 41 | 36 | 32 | 40   | 34 | 30 | 27 | 19  |  |   |    |
|          |           |                 | 0.56            | 1.25          | 68   | 58 | 51 | 45 | 63   | 54 | 47 | 42 | 52   | 46 | 41 | 36 | 43   | 38 | 34 | 31 | 22  |  |   |    |
| 下方投影面積   |           | cm <sup>2</sup> |                 | 1.5           | 72   | 63 | 55 | 50 | 66   | 58 | 52 | 46 | 55   | 49 | 44 | 40 | 46   | 41 | 37 | 34 | 24  |  |   |    |
| 等価発光面積   |           |                 | cm <sup>2</sup> | 2.0           | 77   | 69 | 62 | 57 | 71   | 64 | 58 | 53 | 60   | 54 | 50 | 46 | 49   | 45 | 42 | 39 | 27  |  |   |    |
| 取付<br>高さ | 器具間隔最大限   |                 |                 | 2.5           | 80   | 73 | 67 | 62 | 74   | 68 | 63 | 58 | 62   | 58 | 54 | 50 | 52   | 48 | 45 | 42 | 30  |  |   |    |
|          | 横方向 ( A ) |                 | 縦方向 ( B )       | 3.0           | 83   | 76 | 71 | 66 | 76   | 71 | 66 | 62 | 64   | 60 | 56 | 53 | 53   | 50 | 47 | 45 | 32  |  |   |    |
| H m      | 0.65 H m  | 1.49 H m        |                 | 4.0           | 86   | 81 | 76 | 72 | 79   | 75 | 71 | 67 | 67   | 64 | 61 | 58 | 56   | 53 | 51 | 49 | 35  |  |   |    |
|          |           |                 |                 | 5.0           | 88   | 83 | 79 | 76 | 81   | 77 | 74 | 71 | 69   | 66 | 63 | 61 | 57   | 55 | 53 | 51 | 37  |  |   |    |
|          |           |                 |                 | 7.0           | 90   | 87 | 83 | 80 | 84   | 81 | 78 | 75 | 71   | 69 | 67 | 65 | 59   | 58 | 56 | 54 | 39  |  |   |    |
|          |           |                 |                 | 10.0          | 92   | 89 | 87 | 85 | 85   | 83 | 81 | 79 | 73   | 71 | 69 | 68 | 61   | 60 | 58 | 57 | 41  |  |   |    |

