

屋内照明器具特性

品番 (品名)	XED3 2 2 1 N	
光源	LLD3 0 2 0 NCT1 × 1	795.0 l m
管理番号	K0190493 (0) DR 1	
BZ分類	BZ1	

器具効率	68 %	天井	80 %				70 %				50 %				30 %				0 %						
	上方光束		0 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
下方光束	68 %	床	10 %				10 %				10 %				10 %				0 %						
室指数	照明率 (X 0.01)																			ZCM					
保守率	良	0.63	0.6	0.6	5.6	5.1	4.9	4.7	5.5	5.1	4.8	4.7	5.4	5.1	4.8	4.6	5.3	5.0	4.8	4.6	4.6				
	中	0.6	0.6	0.6	6.0	5.6	5.3	5.1	5.9	5.6	5.3	5.1	5.8	5.5	5.3	5.1	5.7	5.5	5.3	5.1	5.0				
	否	0.56	0.6	0.6	6.3	5.9	5.7	5.5	6.2	5.9	5.6	5.4	6.1	5.8	5.6	5.4	6.0	5.7	5.5	5.4	5.3				
下方投影面積	等価発光面積	c m ²	c m ²	1.25	6.5	6.2	5.9	5.7	6.4	6.1	5.9	5.7	6.3	6.0	5.8	5.7	6.2	6.0	5.8	5.7	5.6				
				1.5	6.6	6.3	6.1	6.0	6.5	6.3	6.1	5.9	6.4	6.2	6.0	5.9	6.3	6.1	6.0	5.8	5.7	5.7			
取付高さ	器具間隔最大限		H m	0.41 H m	H m	0.41 H m	2.5	6.9	6.7	6.6	6.4	6.8	6.7	6.5	6.4	6.7	6.5	6.4	6.3	6.6	6.4	6.3	6.2	6.1	
	横方向 (A)	縦方向 (B)					3.0	7.0	6.8	6.7	6.5	6.9	6.8	6.6	6.5	6.8	6.6	6.5	6.4	6.6	6.5	6.4	6.6	6.5	6.4
H m	0.41 H m	0.41 H m	4.0	7.1	6.9	6.8	6.7	7.0	6.9	6.8	6.7	6.8	6.7	6.7	6.6	6.7	6.6	6.6	6.6	6.6	6.5	6.3	6.3	6.3	
			5.0	7.1	7.0	6.9	6.8	7.0	6.9	6.9	6.8	6.9	6.8	6.7	6.7	6.8	6.7	6.8	6.7	6.6	6.6	6.6	6.6	6.4	6.4
			7.0	7.2	7.1	7.0	6.9	7.1	7.0	7.0	6.9	7.0	6.9	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.7	6.7	6.5	6.5
10.0	7.2	7.2	7.1	7.0	7.1	7.1	7.0	7.0	7.0	6.9	6.9	6.9	6.8	6.8	6.8	6.8	6.8	6.8	6.7	6.7	6.6	6.6	6.6		

