

屋内照明器具特性

品番 (品名)	XED3 2 2 2 N	
光源	LLD3 0 2 0 NCT1 × 1	795.0 l m
管理番号	K0190494 (0) DR 1	
BZ分類	BZ1	

器具効率	71 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
下方光束	71 %	床		10 %				10 %				10 %				10 %				0 %	
室指数	照明率 (X 0.01)																			ZCM	
保守率	良 0.63	0.6	0.6	58	54	51	49	58	53	51	49	57	53	50	49	56	53	50	49	48	
	中		0.8	63	59	56	54	62	58	56	54	61	58	55	54	60	57	55	53	53	
	否 0.56		1.0	65	62	59	57	65	61	59	57	64	61	58	57	62	60	58	57	56	
下方投影面積	cm ²	等価発光面積	cm ²	1.25	68	65	62	60	67	64	62	60	66	63	61	60	65	62	61	59	58
				1.5	69	66	64	62	69	66	64	62	67	65	63	62	66	64	63	61	60
取付高さ	器具間隔最大限		H m	0.41 H m	H m	0.41 H m	2.5	72	70	69	67	72	70	68	67	70	69	67	66	65	64
	横方向 (A)	縦方向 (B)					3.0	73	71	70	69	72	71	69	68	71	69	68	67	69	68
H m	0.41 H m	0.41 H m	4.0	74	73	71	70	73	72	71	70	72	71	70	69	70	69	69	68	66	
			5.0	75	73	72	71	74	73	72	71	72	71	71	70	71	70	69	69	67	
			7.0	75	74	74	73	74	74	73	72	73	72	72	71	71	71	70	70	68	
10.0	76	75	74	74	75	74	74	73	73	73	72	72	72	72	71	71	71	69			

