

屋内照明器具特性	
品番 (品名)	XFL312VSC
光源	LDL40S.N/14/26(2600A) ×1 2600.0lm
管理番号	K0126144(1)DB1
BZ分類	BZ2

器具効率	66%	天井	80%				70%				50%				30%				0%
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	床	10%				10%				10%				10%				0%
下方光束	66%	室指数	照明率 (X0.01)																ZCM
保守率	良 中 否 0.81 0.77 0.68	0.6	44	37	33	30	43	37	33	30	42	36	33	30	41	36	32	30	29
		0.8	51	45	41	38	50	44	40	38	48	44	40	37	47	43	40	37	36
		1.0	55	49	46	43	54	49	45	43	52	48	45	42	51	47	44	42	41
		1.25	58	54	50	47	57	53	50	47	56	52	49	47	54	51	49	47	45
下方投影面積	c m ²	1.5	60	56	53	50	59	56	53	50	58	55	52	50	56	54	51	49	48
		2.0	63	60	57	55	62	59	57	55	61	58	56	54	59	57	55	53	52
取付高さ	器具間隔最大限		2.5	65	62	60	58	64	61	59	57	62	60	58	57	61	59	57	55
	横方向 (A)	縦方向 (B)	3.0	66	64	62	60	65	63	61	59	64	62	60	59	62	60	59	58
1.5m	1.87m	1.91m	4.0	67	66	64	62	67	65	63	62	65	64	62	61	64	62	61	
2	2.48	2.38	5.0	68	67	65	64	67	66	65	64	66	65	64	63	64	63	62	
2.5	3.09	2.86	7.0	69	68	67	66	68	67	66	66	67	66	65	64	65	65	64	
3	3.68	3.35	10.0	70	69	68	68	69	68	68	67	68	67	66	66	66	65	63	

