

屋内照明器具特性

品番 (品名)	XFL323ZPJ														
光源	LDL40S.N/14/26 x2 2600.0 1m														
管理番号	K0189121(1)D 1														
BZ分類	BZ3														

器具効率	75 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	1 %	室指数	照明率 (X0.01)																ZCM		
下方光束	74 %																				
保守率	良 中 否	0.77	0.6	47	39	34	31	47	39	34	31	45	38	34	31	43	38	33	30	29	
		0.72	0.8	55	48	43	39	54	47	42	39	52	46	42	39	50	45	41	39	37	
		0.68	1.0	60	53	48	45	59	52	48	45	57	51	47	44	55	50	47	44	43	
			1.25	64	58	53	50	63	57	53	50	61	56	52	49	59	55	52	49	47	
下方投影面積	c m ²	1.5	66	61	57	54	65	60	56	53	63	59	56	53	61	58	55	52	51		
		2.0	70	65	62	59	69	65	61	59	67	63	60	58	65	62	59	57	56		
取付高さ	器具間隔最大限		2.5	72	68	65	62	71	67	65	62	69	66	63	61	67	65	62	61	59	
	横方向 (A)	縦方向 (B)	3.0	73	70	67	65	72	69	67	65	70	68	66	64	68	66	65	63	61	
1.5m	1.79 m	2.07 m	4.0	75	73	70	68	74	72	70	68	72	70	68	67	70	69	67	66	64	
2	2.38	2.63	5.0	76	74	72	71	75	73	72	70	73	72	70	69	72	70	69	68	66	
2.5	2.96	3.21	7.0	78	76	75	73	77	75	74	73	75	74	72	71	73	72	71	70	68	
3	3.55	3.8	10.0	79	77	76	75	78	77	76	75	76	75	74	73	74	73	73	72	70	

