

屋内照明器具特性

品番 (品名)	XFL326EX	
光源	LDL40S.N/14/26(2600A) ×2 2600.0 1m	
管理番号	K0126501(3)DB1	
BZ分類	BZ3/0.9/BZ2	

器具効率	73%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	0%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	73%																																																						
保守率	良 0.81 中 0.77 否 0.68	0.6	45	37	32	29	44	37	32	28	43	36	32	28	41	35	31	28	27																																				
		0.8	54	47	43	39	53	47	42	39	52	46	42	39	50	45	41	39	37																																				
		1.0	60	54	49	46	59	53	49	46	57	52	48	46	55	51	48	45	44																																				
		1.25	64	59	55	52	63	58	54	52	61	57	54	51	59	56	53	51	49																																				
下方投影面積	c m ²	1.5	66	62	58	55	65	61	58	55	64	60	57	55	62	59	56	54	53																																				
		2.0	70	66	63	61	69	65	63	60	67	64	62	60	65	63	61	59	58																																				
取付高さ	器具間隔最大限		2.5	72	69	66	64	71	68	66	64	69	67	65	63	67	65	64	62	60																																			
	横方向 (A)	縦方向 (B)	3.0	73	70	68	66	72	70	68	66	70	68	66	65	69	67	65	64	62																																			
1.5m	2.73m	2.09m	4.0	75	73	71	69	74	72	70	69	72	70	69	68	70	69	68	67	65																																			
2	3.64	2.64	5.0	75	74	72	71	75	73	72	70	73	72	70	69	71	70	69	68	66																																			
2.5	4.56	3.21	7.0	77	75	74	73	76	75	73	73	74	73	72	71	72	72	71	70	68																																			
3	5.47	3.78	10.0	77	76	76	75	76	76	75	74	75	74	73	73	73	73	72	72	70																																			

