

| | |
|----------|-----------------------------------------|
| 屋内照明器具特性 | |
| 品番 (品名) | XFL326PF |
| 光源 | LDL40S.N/14/26(2600A) ×2 2600.0 1m |
| 管理番号 | K0126224(1)DB1 |
| BZ分類 | BZ5 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|------------------|---------|-------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率 | 66% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| | | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 上方光束 | 0% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 下方光束 | 66% | | | | | | | | | | | | | | | | | | | |
| 保守率 | 良 中 否 | 0.77 | 0.6 | 3.7 | 2.9 | 2.4 | 2.1 | 3.6 | 2.9 | 2.4 | 2.0 | 3.5 | 2.8 | 2.4 | 2.0 | 3.3 | 2.7 | 2.3 | 2.0 | 1.9 |
| | | 0.72 | 0.8 | 4.4 | 3.6 | 3.1 | 2.7 | 4.3 | 3.6 | 3.1 | 2.7 | 4.1 | 3.5 | 3.1 | 2.7 | 3.9 | 3.4 | 3.0 | 2.7 | 2.6 |
| | | | 1.0 | 4.8 | 4.1 | 3.6 | 3.2 | 4.7 | 4.1 | 3.6 | 3.2 | 4.5 | 4.0 | 3.5 | 3.2 | 4.4 | 3.9 | 3.5 | 3.2 | 3.0 |
| | | 0.68 | 1.25 | 5.2 | 4.6 | 4.1 | 3.7 | 5.1 | 4.5 | 4.1 | 3.7 | 4.9 | 4.4 | 4.0 | 3.7 | 4.7 | 4.3 | 3.9 | 3.7 | 3.5 |
| 下方投影面積 | c m ² | 1.5 | 5.5 | 4.9 | 4.5 | 4.1 | 5.4 | 4.9 | 4.4 | 4.1 | 5.2 | 4.7 | 4.4 | 4.1 | 5.0 | 4.6 | 4.3 | 4.0 | 3.9 | |
| | | 2.0 | 5.9 | 5.4 | 5.0 | 4.7 | 5.8 | 5.3 | 4.9 | 4.6 | 5.6 | 5.2 | 4.9 | 4.6 | 5.4 | 5.0 | 4.8 | 4.5 | 4.4 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 6.1 | 5.7 | 5.3 | 5.0 | 6.0 | 5.6 | 5.3 | 5.0 | 5.8 | 5.5 | 5.2 | 4.9 | 5.6 | 5.3 | 5.1 | 4.9 | 4.7 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 6.3 | 5.9 | 5.6 | 5.3 | 6.2 | 5.8 | 5.5 | 5.3 | 6.0 | 5.7 | 5.4 | 5.2 | 5.8 | 5.5 | 5.3 | 5.1 | 5.0 |
| 1.5m | 1.94m | 2.18m | 4.0 | 6.5 | 6.2 | 5.9 | 5.7 | 6.4 | 6.1 | 5.9 | 5.7 | 6.2 | 6.0 | 5.8 | 5.6 | 6.0 | 5.8 | 5.6 | 5.5 | 5.3 |
| 2 | 2.57 | 2.75 | 5.0 | 6.6 | 6.3 | 6.1 | 5.9 | 6.5 | 6.3 | 6.1 | 5.9 | 6.3 | 6.1 | 6.0 | 5.8 | 6.1 | 6.0 | 5.8 | 5.7 | 5.5 |
| 2.5 | 3.19 | 3.34 | 7.0 | 6.7 | 6.6 | 6.4 | 6.2 | 6.6 | 6.5 | 6.3 | 6.2 | 6.5 | 6.3 | 6.2 | 6.1 | 6.3 | 6.2 | 6.1 | 6.0 | 5.8 |
| 3 | 3.81 | 3.94 | 10.0 | 6.8 | 6.7 | 6.6 | 6.5 | 6.7 | 6.6 | 6.5 | 6.4 | 6.6 | 6.5 | 6.4 | 6.3 | 6.4 | 6.3 | 6.3 | 6.2 | 6.0 |

