

屋内照明器具特性	
品番 (品名)	XFL814B
光源	LDL110S.N/54/65K(6500) ×1 6500.0 1m
管理番号	K0129360(1)DB1
BZ分類	BZ5/1.1/BZ4

器具効率	93%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	93%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	5.3	4.2	3.4	2.9	5.2	4.1	3.4	2.9	5.0	4.0	3.4	2.9	4.8	3.9	3.3	2.9	2.7
	中	0.77	0.8	6.3	5.2	4.5	4.0	6.1	5.1	4.4	3.9	5.9	5.0	4.4	3.9	5.7	4.9	4.3	3.9	3.7
	否	0.68	1.0	6.9	5.9	5.2	4.7	6.8	5.9	5.2	4.7	6.5	5.7	5.1	4.6	6.3	5.6	5.0	4.6	4.4
			1.25	7.5	6.6	6.0	5.4	7.4	6.5	5.9	5.4	7.1	6.4	5.8	5.4	6.8	6.2	5.7	5.3	5.1
下方投影面積		cm ²	1.5	7.9	7.1	6.5	6.0	7.8	7.0	6.4	6.0	7.5	6.8	6.3	5.9	7.2	6.7	6.2	5.9	5.6
等価発光面積		cm ²	2.0	8.4	7.8	7.3	6.8	8.3	7.7	7.2	6.8	8.0	7.5	7.1	6.7	7.8	7.3	6.9	6.6	6.4
取付高さ	器具間隔最大限		2.5	8.8	8.2	7.7	7.3	8.6	8.1	7.7	7.3	8.4	7.9	7.5	7.2	8.1	7.7	7.4	7.1	6.9
	横方向 (A)	縦方向 (B)	3.0	9.0	8.5	8.1	7.7	8.9	8.4	8.0	7.7	8.6	8.2	7.9	7.6	8.3	8.0	7.7	7.5	7.3
1.5m	2.1m	2.9m	4.0	9.3	8.9	8.6	8.3	9.1	8.8	8.5	8.2	8.9	8.6	8.3	8.1	8.6	8.4	8.2	8.0	7.7
2	2.73	3.32	5.0	9.4	9.1	8.9	8.6	9.3	9.0	8.8	8.5	9.1	8.8	8.6	8.4	8.8	8.6	8.4	8.3	8.0
2.5	3.37	3.83	7.0	9.6	9.4	9.2	9.0	9.5	9.3	9.1	8.9	9.3	9.1	8.9	8.8	9.0	8.9	8.8	8.6	8.4
3	4.01	4.36	10.0	9.8	9.6	9.5	9.3	9.7	9.5	9.4	9.2	9.4	9.3	9.2	9.1	9.2	9.1	9.0	8.9	8.6

