

屋内照明器具特性	
品番 (品名)	NY Y 7 1 0 5 3 + N T S 9 0 1 5 0
光源	L E D 3 0 0 0 _ 7 0 _ 2 1 5 × 1 2 1 5 . 0 l m
管理番号	K 0 1 5 2 4 4 7 (6) D J 1
B Z 分類	B Z 1

器具効率		1 0 6 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																Z C M	
下方光束		1 0 6 %																			
保守率		良	0 . 6 7	0 . 6	1 0 8	1 0 6	1 0 4	1 0 4	1 0 7	1 0 5	1 0 4	1 0 3	1 0 7	1 0 5	1 0 4	1 0 3	1 0 6	1 0 5	1 0 4	1 0 3	1 0 3
		中	0 . 6 3	0 . 8	1 0 9	1 0 7	1 0 6	1 0 5	1 0 8	1 0 7	1 0 5	1 0 5	1 0 8	1 0 6	1 0 5	1 0 4	1 0 7	1 0 6	1 0 5	1 0 4	1 0 3
		否	0 . 5 6	1 . 0	1 1 0	1 0 8	1 0 7	1 0 6	1 0 9	1 0 8	1 0 6	1 0 5	1 0 8	1 0 7	1 0 6	1 0 5	1 0 7	1 0 6	1 0 5	1 0 5	1 0 4
下方投影面積		c m ²	1 . 2 5	1 1 1	1 0 9	1 0 7	1 0 6	1 1 0	1 0 8	1 0 7	1 0 6	1 0 9	1 0 7	1 0 6	1 0 6	1 0 8	1 0 7	1 0 6	1 0 5	1 0 4	
			1 . 5	1 1 1	1 0 9	1 0 8	1 0 7	1 1 0	1 0 9	1 0 8	1 0 7	1 0 9	1 0 8	1 0 7	1 0 6	1 0 8	1 0 7	1 0 6	1 0 5	1 0 4	
等価発光面積		c m ²	2 . 0	1 1 2	1 1 0	1 0 9	1 0 8	1 1 1	1 1 0	1 0 9	1 0 8	1 0 9	1 0 8	1 0 8	1 0 7	1 0 8	1 0 7	1 0 7	1 0 6	1 0 5	
			2 . 5	1 1 2	1 1 1	1 1 0	1 0 9	1 1 1	1 1 0	1 0 9	1 0 9	1 1 0	1 0 9	1 0 8	1 0 8	1 0 8	1 0 7	1 0 7	1 0 6	1 0 5	
取付 高さ	器具間隔最大限		3 . 0	1 1 3	1 1 2	1 1 1	1 1 0	1 1 2	1 1 1	1 1 0	1 0 9	1 1 0	1 0 9	1 0 9	1 0 8	1 0 8	1 0 8	1 0 7	1 0 7	1 0 5	
	横方向 (A)	縦方向 (B)	4 . 0	1 1 3	1 1 2	1 1 1	1 1 1	1 1 2	1 1 1	1 1 1	1 1 0	1 1 0	1 1 0	1 0 9	1 0 9	1 0 8	1 0 8	1 0 7	1 0 7	1 0 5	
H m	0 . 1 6 H m	0 . 1 6 H m	5 . 0	1 1 3	1 1 3	1 1 2	1 1 1	1 1 2	1 1 2	1 1 1	1 1 1	1 1 0	1 1 0	1 0 9	1 0 9	1 0 8	1 0 8	1 0 8	1 0 7	1 0 5	
			7 . 0	1 1 4	1 1 3	1 1 3	1 1 2	1 1 3	1 1 2	1 1 2	1 1 1	1 1 0	1 1 0	1 1 0	1 0 9	1 0 8	1 0 8	1 0 8	1 0 8	1 0 5	
			1 0 . 0	1 1 4	1 1 4	1 1 3	1 1 3	1 1 3	1 1 2	1 1 2	1 1 2	1 1 1	1 1 0	1 1 0	1 1 0	1 0 9	1 0 8	1 0 8	1 0 8	1 0 5	

