

# 屋内照明器具特性

品番 (品名)	S Q - L D 5 2 5 - K	
光源	LED6200_70_1025 ×1	1025.0 lm
管理番号	K0157897 ( 0 ) DB 1	
B Z 分類	B Z 5 / 1 . 1 / B Z 4	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
下方光束	100 %	床		10 %				10 %				10 %				10 %				0 %			
室指数			照明率 ( X 0 . 0 1 )																				Z C M
保守率	良	0.69	0.6	5.7	4.5	3.7	3.2	5.6	4.4	3.7	3.2	5.3	4.3	3.6	3.2	5.1	4.2	3.6	3.1	2.9			
	中	0.67	0.8	6.7	5.6	4.8	4.3	6.6	5.5	4.8	4.2	6.3	5.4	4.7	4.2	6.1	5.3	4.7	4.2	4.0			
	否	0.63	1.0	7.4	6.4	5.6	5.0	7.3	6.3	5.6	5.0	7.0	6.1	5.5	5.0	6.7	6.0	5.4	5.0	4.7			
			1.25	8.0	7.1	6.4	5.8	7.9	7.0	6.3	5.8	7.6	6.8	6.2	5.8	7.3	6.6	6.1	5.7	5.5			
下方投影面積		cm <sup>2</sup>	1.5	8.5	7.6	6.9	6.4	8.3	7.5	6.9	6.4	8.0	7.3	6.8	6.3	7.7	7.1	6.7	6.3	6.0			
等価発光面積		cm <sup>2</sup>	2.0	9.0	8.3	7.7	7.3	8.9	8.2	7.7	7.2	8.6	8.0	7.5	7.1	8.3	7.8	7.4	7.1	6.8			
取付高さ	器具間隔最大限		2.5	9.4	8.8	8.3	7.8	9.2	8.7	8.2	7.8	8.9	8.5	8.1	7.7	8.7	8.3	7.9	7.6	7.4			
	横方向 (A)	縦方向 (B)	3.0	9.6	9.1	8.7	8.3	9.5	9.0	8.6	8.2	9.2	8.8	8.4	8.1	8.9	8.6	8.3	8.0	7.7			
H m	1.27 H m	1.27 H m	4.0	9.9	9.5	9.2	8.8	9.8	9.4	9.1	8.8	9.5	9.2	8.9	8.7	9.2	9.0	8.7	8.5	8.3			
			5.0	10.1	9.8	9.5	9.2	10.0	9.7	9.4	9.1	9.7	9.4	9.2	9.0	9.5	9.2	9.0	8.9	8.6			
			7.0	10.3	10.1	9.9	9.6	10.2	10.0	9.8	9.6	9.9	9.7	9.6	9.4	9.7	9.5	9.4	9.2	9.0			
			10.0	10.5	10.3	10.1	10.0	10.3	10.2	10.0	9.9	10.1	10.0	9.8	9.7	9.9	9.8	9.6	9.5	9.3			

