

屋内照明器具特性

品番 (品名)

NY Y 7 1 0 6 0 + N T S 9 0 2 0 0

光源

L E D 3 5 0 0 _ 7 0 _ 7 1 0 × 1 7 1 0 . 0 l m

管理番号

K 0 1 5 2 4 5 0 (*) D J 1

B Z 分類

B Z 1

器具効率

1 0 2 %

上方光束

0 %

下方光束

1 0 2 %

天井
壁
床

8 0 %

7 0 %

5 0 %

3 0 %

0 %

7 0

5 0

3 0

1 0

7 0

5 0

3 0

1 0

7 0

5 0

3 0

1 0

0 %

1 0 %

1 0 %

1 0 %

1 0 %

0 %

室指数

照明率 (× 0 . 0 1)

Z C M

保守率

良 0 . 6 7

中 0 . 6 3

否 0 . 5 6

下方投影面積

c m²

等価発光面積

c m²

取付

器具間隔最大限

高さ

横方向 (A)

縦方向 (B)

H m

0 . 2 8 H m

0 . 2 8 H m

0 . 6	1 0 1	9 9	9 7	9 6	1 0 1	9 9	9 7	9 6	1 0 0	9 8	9 7	9 6	1 0 0	9 8	9 7	9 6	9 5
0 . 8	1 0 3	1 0 1	9 9	9 8	1 0 3	1 0 1	9 9	9 8	1 0 2	1 0 0	9 9	9 8	1 0 1	9 9	9 8	9 7	9 7
1 . 0	1 0 4	1 0 2	1 0 1	1 0 0	1 0 4	1 0 2	1 0 0	9 9	1 0 3	1 0 1	1 0 0	9 9	1 0 2	1 0 0	9 9	9 9	9 8
1 . 2 5	1 0 5	1 0 3	1 0 2	1 0 1	1 0 5	1 0 3	1 0 2	1 0 1	1 0 4	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	1 0 1	1 0 0	9 9
1 . 5	1 0 6	1 0 4	1 0 3	1 0 2	1 0 6	1 0 4	1 0 3	1 0 2	1 0 5	1 0 3	1 0 2	1 0 1	1 0 3	1 0 2	1 0 1	1 0 0	9 9
2 . 0	1 0 7	1 0 6	1 0 4	1 0 3	1 0 7	1 0 6	1 0 5	1 0 4	1 0 6	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 0
2 . 5	1 0 8	1 0 6	1 0 5	1 0 4	1 0 8	1 0 6	1 0 5	1 0 4	1 0 5	1 0 4	1 0 3	1 0 3	1 0 4	1 0 3	1 0 2	1 0 2	1 0 0
3 . 0	1 0 8	1 0 7	1 0 6	1 0 5	1 0 8	1 0 7	1 0 6	1 0 5	1 0 4	1 0 5	1 0 4	1 0 3	1 0 4	1 0 3	1 0 3	1 0 2	1 0 0
4 . 0	1 0 9	1 0 8	1 0 7	1 0 6	1 0 9	1 0 8	1 0 7	1 0 6	1 0 5	1 0 6	1 0 5	1 0 4	1 0 4	1 0 4	1 0 3	1 0 3	1 0 0
5 . 0	1 0 9	1 0 8	1 0 7	1 0 7	1 0 9	1 0 8	1 0 7	1 0 7	1 0 6	1 0 6	1 0 5	1 0 5	1 0 4	1 0 4	1 0 4	1 0 3	1 0 1
7 . 0	1 0 9	1 0 9	1 0 8	1 0 8	1 0 9	1 0 8	1 0 8	1 0 7	1 0 7	1 0 6	1 0 6	1 0 5	1 0 5	1 0 4	1 0 4	1 0 4	1 0 1
1 0 . 0	1 1 0	1 0 9	1 0 9	1 0 8	1 0 8	1 0 8	1 0 8	1 0 7	1 0 6	1 0 6	1 0 6	1 0 6	1 0 4	1 0 4	1 0 4	1 0 4	1 0 1

配光曲線

ランプ光束 1 0 0 0 l m

— 管軸に垂直 (A)
- - - 管軸に平行 (B)

直射水平面照度

ランプ光束 1 0 0 0 l m

8 0 lx X 1 0 0

6 0

4 0

2 0

1 0

8

6

4

2

1

0.5

0.2

0.1

0.05

0.02

0.01

0.005

0.002

0.001

0.0005

0.0002

0.0001

0.00005

0.00002

0.00001

0.000005

0.000002

0.000001

H = 1 . 5

H = 2

H = 2 . 5

H = 3

H = 4

H = 5