

屋内照明器具特性	
品番 (品名)	NY Y 7 1 0 6 4 + NY Y 9 0 1 5 0
光源	LED 4 0 0 0 _ 7 0 _ 6 0 5 x 1 6 0 5 . 0 l m
管理番号	K 0 1 5 2 4 5 0 (*) DJ 1
B Z 分類	B Z 1

器具効率		1 0 2 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																Z C M			
下方光束		1 0 2 %																					
保守率		良	0 . 6 7	0 . 6	1 0 1	9 9	9 7	9 6	1 0 1	9 9	9 7	9 6	1 0 0	9 8	9 7	9 6	1 0 0	9 8	9 7	9 6	9 5		
		中	0 . 6 3	0 . 8	1 0 3	1 0 1	9 9	9 8	1 0 3	1 0 1	9 9	9 8	1 0 2	1 0 0	9 9	9 8	1 0 1	9 9	9 8	9 7	9 7		
		否	0 . 5 6	1 . 0	1 0 4	1 0 2	1 0 1	1 0 0	1 0 4	1 0 2	1 0 0	9 9	1 0 3	1 0 1	1 0 0	9 9	1 0 2	1 0 0	9 9	9 9	9 8		
下方投影面積		c m ²	1 . 2 5	1 0 5	1 0 3	1 0 2	1 0 1	1 0 5	1 0 3	1 0 2	1 0 1	1 0 4	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 8		
			1 . 5	1 0 6	1 0 4	1 0 3	1 0 2	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 3	1 0 2	1 0 1	1 0 3	1 0 2	1 0 1	1 0 0	9 9	9 9		
等価発光面積		c m ²	2 . 0	1 0 7	1 0 6	1 0 4	1 0 3	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 1	1 0 0	9 9		
			2 . 5	1 0 8	1 0 6	1 0 5	1 0 4	1 0 7	1 0 6	1 0 5	1 0 4	1 0 5	1 0 4	1 0 3	1 0 3	1 0 4	1 0 3	1 0 2	1 0 2	1 0 1	1 0 0		
取付 高さ	器具間隔最大限		3 . 0	1 0 8	1 0 7	1 0 6	1 0 5	1 0 7	1 0 6	1 0 5	1 0 4	1 0 5	1 0 5	1 0 4	1 0 3	1 0 4	1 0 3	1 0 3	1 0 2	1 0 1	1 0 0		
	横方向 (A)	縦方向 (B)	4 . 0	1 0 9	1 0 8	1 0 7	1 0 6	1 0 8	1 0 7	1 0 6	1 0 5	1 0 6	1 0 5	1 0 4	1 0 4	1 0 4	1 0 3	1 0 3	1 0 3	1 0 2	1 0 0		
H m	0 . 2 8 H m	0 . 2 8 H m	5 . 0	1 0 9	1 0 8	1 0 7	1 0 7	1 0 8	1 0 7	1 0 7	1 0 6	1 0 6	1 0 5	1 0 5	1 0 4	1 0 4	1 0 4	1 0 3	1 0 3	1 0 1	1 0 0		
			7 . 0	1 0 9	1 0 9	1 0 8	1 0 8	1 0 8	1 0 8	1 0 7	1 0 7	1 0 6	1 0 6	1 0 5	1 0 5	1 0 4	1 0 4	1 0 4	1 0 3	1 0 1	1 0 0		
			1 0 . 0	1 1 0	1 0 9	1 0 9	1 0 8	1 0 8	1 0 8	1 0 8	1 0 7	1 0 6	1 0 6	1 0 6	1 0 6	1 0 4	1 0 4	1 0 4	1 0 4	1 0 1	1 0 0		

