

# 屋内照明器具特性

品番 (品名)	XAS 5000 V														
光源	LLD5000VCC1 ×1                      1140.0 l m														
管理番号	K0187895 ( 0 ) DR 1														
B Z 分類	B Z 2														

器具効率	89 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	0 %	室指数	照明率 ( X0.01 )															ZCM			
下方光束	89 %																				
保守率	良 中 否	0.67	0.6	60	51	45	42	59	51	45	42	57	50	45	41	56	49	45	41	40	
		0.63	0.8	69	61	56	52	68	61	56	52	66	60	55	52	64	59	55	51	50	
			1.0	75	68	63	59	74	67	62	59	72	66	62	58	70	65	61	58	57	
		0.56	1.25	79	73	69	65	78	72	68	65	76	71	67	64	74	70	67	64	62	
下方投影面積	c m <sup>2</sup>	1.5	82	77	72	69	81	76	72	69	79	75	71	68	77	73	70	68	66		
		2.0	86	81	78	75	85	81	77	74	82	79	76	74	80	78	75	73	71		
取付高さ	器具間隔最大限		2.5	88	84	81	79	87	84	81	78	85	82	79	77	83	80	78	76	74	
	横方向 ( A )	縦方向 ( B )	3.0	90	86	84	81	88	85	83	81	86	84	82	80	84	82	80	79	77	
H m	1.25 H m	1.25 H m	4.0	91	89	87	85	90	88	86	84	88	86	84	83	86	85	83	82	80	
			5.0	93	90	89	87	91	90	88	86	89	88	86	85	87	86	85	84	81	
			7.0	94	92	91	90	93	91	90	89	91	89	88	87	89	88	87	86	83	
			10.0	95	94	93	92	94	93	92	91	92	91	90	89	90	89	88	88	85	

