

屋内照明器具特性

| | | | | | | | | | | |
|---------|-------------------|--|--|--|--|----------|--|--|--|--|
| 品番 (品名) | SLR1310N | | | | | | | | | |
| 光源 | LED5000_70_328 x1 | | | | | 328.0 lm | | | | |
| 管理番号 | K0167071(0)DB1 | | | | | | | | | |
| BZ分類 | BZ4/0.7/BZ3 | | | | | | | | | |

| | | | | | | | | | | | | | | | | | | | | | |
|--------|---------------|---------|-----------------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|----|-----|----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | | |
| | 上方光束 | | 0% | 反射率 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| | 下方光束 | | 100% | | 壁 | 10% | | | | 10% | | | | 10% | | | | 10% | | | |
| 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.69 | 0.6 | 61 | 49 | 42 | 37 | 59 | 49 | 42 | 37 | 57 | 48 | 41 | 37 | 55 | 47 | 41 | 37 | 35 | |
| | 中 | 0.67 | 0.8 | 71 | 61 | 54 | 49 | 70 | 60 | 53 | 49 | 67 | 59 | 53 | 48 | 65 | 58 | 52 | 48 | 46 | |
| | 否 | 0.63 | 1.0 | 78 | 69 | 62 | 57 | 77 | 68 | 62 | 57 | 74 | 66 | 61 | 56 | 72 | 65 | 60 | 56 | 54 | |
| | | | 0.63 | 1.25 | 84 | 76 | 69 | 65 | 82 | 75 | 69 | 64 | 80 | 73 | 68 | 64 | 77 | 72 | 67 | 63 | 61 |
| 下方投影面積 | | | cm ² | 1.5 | 88 | 80 | 75 | 70 | 86 | 79 | 74 | 70 | 84 | 78 | 73 | 69 | 81 | 76 | 72 | 69 | 66 |
| | 等価発光面積 | | cm ² | 2.0 | 93 | 87 | 82 | 78 | 91 | 86 | 81 | 78 | 89 | 84 | 80 | 77 | 86 | 82 | 79 | 76 | 74 |
| 取付高さ | 器具間隔最大限 | | | 2.5 | 96 | 91 | 87 | 83 | 95 | 90 | 86 | 83 | 92 | 88 | 85 | 82 | 89 | 86 | 83 | 81 | 78 |
| | 横方向 (A) | 縦方向 (B) | | 3.0 | 98 | 94 | 90 | 87 | 97 | 93 | 89 | 86 | 94 | 91 | 88 | 85 | 92 | 89 | 86 | 84 | 82 |
| Hm | 1.12Hm | 1.10Hm | | 4.0 | 101 | 97 | 94 | 92 | 99 | 96 | 93 | 91 | 97 | 94 | 92 | 90 | 94 | 92 | 90 | 88 | 86 |
| | | | | 5.0 | 102 | 99 | 97 | 95 | 101 | 98 | 96 | 94 | 98 | 96 | 94 | 92 | 96 | 94 | 93 | 91 | 88 |
| | | | | 7.0 | 104 | 102 | 100 | 98 | 103 | 101 | 99 | 97 | 100 | 99 | 97 | 96 | 98 | 97 | 95 | 94 | 91 |
| | | | | 10.0 | 105 | 104 | 102 | 101 | 104 | 103 | 101 | 100 | 102 | 100 | 99 | 98 | 99 | 98 | 97 | 97 | 94 |

