

屋内照明器具特性	
品番 (品名)	S L D 1 0 3 6 V
光源	L E D 3 5 0 0 _ 7 0 _ 3 7 5 × 1 3 7 5 . 0 l m
管理番号	K 0 1 4 7 6 3 7 (0) D B 1
B Z 分類	B Z 1

器具効率		1 0 1 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束		1 0 1 %	室指数	照明率 (X 0 . 0 1) Z C M																	
下方光束																					
保守率		良 中 否	0 . 6	8 4	7 8	7 4	7 2	8 4	7 8	7 4	7 1	8 2	7 7	7 4	7 1	8 1	7 7	7 3	7 1	7 0	
			0 . 8	9 1	8 5	8 2	7 9	9 0	8 5	8 1	7 9	8 8	8 4	8 1	7 8	8 7	8 3	8 0	7 8	7 7	
			1 . 0	9 4	9 0	8 6	8 4	9 3	8 9	8 6	8 3	9 2	8 8	8 5	8 3	9 0	8 7	8 5	8 3	8 1	
			0 . 5 6	1 . 2 5	9 7	9 3	9 0	8 8	9 6	9 3	9 0	8 7	9 5	9 1	8 9	8 7	9 3	9 0	8 8	8 6	8 5
下方投影面積		c m ²	1 . 5	9 9	9 6	9 3	9 1	9 8	9 5	9 2	9 0	9 7	9 4	9 1	9 0	9 5	9 3	9 1	8 9	8 7	
等価発光面積			c m ²	2 . 0	1 0 2	9 9	9 6	9 4	1 0 1	9 8	9 6	9 4	9 9	9 7	9 5	9 3	9 7	9 5	9 4	9 2	9 1
2 . 5	1 0 3			1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 6	1 0 0	9 8	9 7	9 5	9 8	9 7	9 6	9 4	9 2		
取付 高さ	器具間隔最大限		3 . 0	1 0 4	1 0 2	1 0 0	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 1	1 0 0	9 8	9 7	9 9	9 8	9 7	9 6	9 4	
	横方向 (A)	縦方向 (B)	4 . 0	1 0 6	1 0 4	1 0 2	1 0 1	1 0 4	1 0 3	1 0 2	1 0 0	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 8	9 5	
H m	0 . 5 0 H m	0 . 5 0 H m	5 . 0	1 0 6	1 0 5	1 0 4	1 0 2	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 9	9 6	
			7 . 0	1 0 7	1 0 6	1 0 5	1 0 4	1 0 6	1 0 5	1 0 4	1 0 3	1 0 4	1 0 3	1 0 2	1 0 2	1 0 2	1 0 1	1 0 1	1 0 0	9 7	
			1 0 . 0	1 0 8	1 0 7	1 0 6	1 0 6	1 0 7	1 0 6	1 0 5	1 0 5	1 0 4	1 0 4	1 0 3	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	9 8	

