

屋内照明器具特性																					
品番（品名）		S L W8 0 0 1 1																			
光源		LDA4 L - H - E17 / S / 4 ×1440.0 l m																			
管理番号		K0183095（0）DR1																			
B Z 分類		B Z 10																			
器具効率 上方光束 下方光束		26 % 26 % 0 %	天井 壁 床	80 %				70 %				50 %				30 %				0 %	
				70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				10 %				10 %				10 %				10 %				0 %	
			室指数	照明率（ X0.01）Z C M																	
保守率		良 中 否	0.63 0.6 0.56	0.6	11	8	6	5	9	7	6	5	6	5	4	3	3	3	2	2	0
				0.8	13	10	8	7	11	9	7	6	7	6	5	4	4	3	3	2	0
下方投影面積 等価発光面積		c m ² c m ²	1.0	14	12	10	9	12	10	9	8	8	7	6	5	4	4	3	3	0	
			1.25	15	13	12	10	13	11	10	9	9	8	7	6	5	4	4	4	0	
取付 高さ		器具間隔最大限 横方向（A）縦方向（B）		1.5	16	14	13	12	14	12	11	10	9	8	8	7	5	5	4	4	0
				2.0	18	16	15	13	15	14	13	12	10	9	9	8	6	5	5	5	0
H m		0.20 H m0.20 H m		2.5	18	17	16	15	16	15	14	13	11	10	9	9	6	6	5	5	0
				3.0	19	18	17	16	16	15	14	14	11	10	10	9	6	6	6	5	0
				4.0	20	19	18	17	17	16	15	15	12	11	11	10	7	6	6	0	
				5.0	20	19	19	18	17	17	16	15	12	11	11	11	7	7	6	6	0
				7.0	21	20	19	19	18	17	17	16	12	12	12	11	7	7	7	0	
				10.0	21	21	20	20	18	18	17	17	12	12	12	12	7	7	7	7	0
配光曲線 ランプ光束1000 l m				直射水平面照度 ランプ光束1000 l m																	
				80 lx																	
				60																	
				40																	
				20																	
				10																	
				8																	
				6																	
				4																	
				2																	
				.8																	
.6																					
.4																					
.2																					
				8 m64202468																	