

屋内照明器具特性

品番 (品名)	XF X4 1 0 S E D									
光源	LED6500_85_1900 x1					1900.0 1 m				
管理番号	K0192149 (0) D 1									
B Z 分類	B Z 5									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %			
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10				
上方光束	0 %	反射率																				
下方光束	100 %	床	10 %				10 %				10 %				10 %				0 %			
		室指数	照明率 (X0.01) ZCM																			
保守率	良	0.81	0.6	5.6	4.4	3.6	3.0	5.5	4.3	3.6	3.0	5.2	4.2	3.5	3.0	5.0	4.1	3.5	3.0	2.8		
	中	0.77	0.8	6.6	5.4	4.6	4.1	6.5	5.4	4.6	4.1	6.2	5.2	4.5	4.0	5.9	5.1	4.5	4.0	3.8		
	否	0.68	1.0	7.3	6.2	5.4	4.8	7.1	6.1	5.3	4.8	6.8	5.9	5.3	4.7	6.5	5.8	5.2	4.7	4.5		
			1.25	7.9	6.9	6.1	5.5	7.7	6.8	6.1	5.5	7.4	6.6	6.0	5.5	7.1	6.4	5.9	5.4	5.2		
下方投影面積		cm ²	1.5	8.3	7.4	6.7	6.1	8.1	7.3	6.6	6.1	7.8	7.1	6.5	6.0	7.5	6.9	6.4	6.0	5.7		
等価発光面積		cm ²	2.0	8.9	8.1	7.5	7.0	8.7	8.0	7.4	6.9	8.4	7.8	7.3	6.8	8.1	7.6	7.1	6.7	6.5		
取付高さ	器具間隔最大限		2.5	9.2	8.6	8.0	7.5	9.1	8.4	7.9	7.5	8.7	8.2	7.8	7.4	8.4	8.0	7.6	7.3	7.0		
	横方向 (A)	縦方向 (B)	3.0	9.5	8.9	8.4	8.0	9.3	8.8	8.3	7.9	9.0	8.5	8.2	7.8	8.7	8.3	8.0	7.7	7.4		
1.5m	1.97 m	2.11 m	4.0	9.8	9.3	8.9	8.6	9.6	9.2	8.8	8.5	9.3	9.0	8.7	8.4	9.1	8.8	8.5	8.2	8.0		
2	2.59	2.65	5.0	10.0	9.6	9.3	9.0	9.8	9.5	9.2	8.9	9.6	9.3	9.0	8.7	9.3	9.0	8.8	8.6	8.3		
2.5	3.23	3.21	7.0	10.2	9.9	9.7	9.4	10.1	9.8	9.6	9.3	9.8	9.6	9.4	9.2	9.5	9.4	9.2	9.0	8.7		
3	3.85	3.79	10.0	10.4	10.2	10.0	9.8	10.3	10.1	9.9	9.7	10.0	9.8	9.7	9.5	9.7	9.6	9.5	9.4	9.1		

