

屋内照明器具特性	
品番 (品名)	S P L 5 5 1 3 F
光源	LDA7 L - H / S / 6 × 5 810.0 l m
管理番号	K0178896 (0) DB 1
B Z 分類	B Z 6

器具効率		94 % 上方光束 17 % 下方光束 77 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.67	0.6	48	36	28	23	46	35	27	22	42	32	26	21	38	30	24	20	17
			0.63	0.8	56	44	37	31	54	43	36	30	49	40	33	29	45	37	31	27	24
			0.56	1.0	62	51	43	37	59	49	41	36	54	45	39	34	49	42	37	32	28
				1.25	67	57	49	43	64	55	48	42	59	51	45	40	54	47	42	38	33
下方投影面積 等価発光面積		c m ² c m ²	1.5	71	61	54	48	68	59	52	47	62	55	49	44	57	51	46	42	37	
			2.0	76	68	61	56	73	66	59	54	67	61	56	51	62	57	52	48	43	
			2.5	80	73	66	61	77	70	64	60	71	65	60	56	65	61	57	53	47	
取付 高さ	器具間隔最大限		2.5	80	73	66	61	77	70	64	60	71	65	60	56	65	61	57	53	47	
	横方向 (A)	縦方向 (B)	3.0	82	76	70	65	79	73	68	64	73	68	64	60	67	63	60	57	51	
H m	1.23 H m	1.23 H m	4.0	86	80	76	71	82	78	73	69	76	72	69	65	71	67	64	62	55	
			5.0	88	83	79	75	85	80	77	73	79	75	72	69	73	70	67	65	58	
			7.0	90	87	83	80	87	84	81	78	81	78	76	74	75	73	71	69	62	
			10.0	92	90	87	85	89	87	84	82	83	81	79	77	78	76	74	73	66	

