

屋内照明器具特性	
品番 (品名)	S N C X 3 1 1 2 1
光源	LED6200_70_4299 ×1 4299.0 lm
管理番号	K0182585 (0) DR 1
B Z 分類	B Z 5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		6 % 94 %	室指数	照明率 (X0.01) ZCM																		
保守率		良 中 否	0.63	0.6	0.6	55	43	35	30	54	42	35	29	51	41	34	29	48	39	33	29	26
			0.6	0.8	65	54	46	40	63	53	45	40	60	51	44	39	57	49	43	38	36	
			0.56	1.0	72	61	53	47	70	60	53	47	66	58	51	46	63	55	50	45	42	
			1.25	78	68	61	55	76	67	60	54	72	64	58	53	68	62	57	52	49		
下方投影面積		cm ²	1.5	82	73	66	61	80	72	65	60	76	69	63	59	72	66	62	58	54		
等価発光面積			2.0	88	80	74	69	86	79	73	68	82	76	71	67	78	73	69	65	62		
取付	器具間隔最大限			2.5	91	85	79	75	89	83	78	74	85	80	76	72	81	77	74	70	67	
高さ	横方向 (A)		縦方向 (B)	3.0	94	88	83	79	92	87	82	78	88	83	80	76	84	80	77	74	70	
H m	1.30 H m		1.30 H m	4.0	97	92	89	85	95	91	87	84	91	87	84	82	87	84	82	79	75	
				5.0	99	95	92	89	97	93	90	87	93	90	87	85	89	87	85	83	79	
				7.0	101	98	96	93	99	97	94	92	95	93	91	89	92	90	88	87	82	
				10.0	103	101	99	97	101	99	97	96	97	96	94	93	94	92	91	90	85	

