

屋内照明器具特性	
品番 (品名)	S N P 5 1 0 0 V
光源	LDA7WW- G- E17 / S / K6 ×1 760.0 l m
管理番号	K0199310 (1) DR 1
B Z 分類	BZ5 / 1.4 / BZ4

器具効率		62 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.67	0.6	34	26	21	18	33	26	21	18	32	25	21	18	30	24	20	17	16
			0.63	0.8	41	34	29	25	40	33	28	25	38	32	28	25	37	31	28	25	23
			0.56	1.0	46	39	34	30	45	38	34	30	43	37	33	30	41	36	33	30	28
				1.25	50	44	39	36	49	43	39	35	47	42	38	35	45	41	37	35	33
下方投影面積		c m ²		1.5	52	47	43	39	51	46	42	39	49	45	42	39	48	44	41	38	37
等価発光面積			c m ²	2.0	56	52	48	45	55	51	48	45	53	50	47	44	51	48	46	44	42
				2.5	58	55	51	49	57	54	51	48	55	52	50	48	54	51	49	47	45
				3.0	60	57	54	51	59	56	53	51	57	54	52	50	55	53	51	49	48
H m	1.58 H m	1.58 H m		4.0	62	59	57	55	61	58	56	54	59	57	55	54	57	56	54	53	51
			5.0	63	61	59	57	62	60	58	57	60	59	57	56	58	57	56	55	53	
			7.0	64	63	61	60	63	62	60	59	62	60	59	58	60	59	58	57	55	
			10.0	65	64	63	62	64	63	62	61	63	62	61	60	61	60	60	59	57	

