

# 屋内照明器具特性

品番 (品名)	XED1101L	
光源	LLD2000LCT1 ×1	531.0 lm
管理番号	K0190473(0)DR1	
BZ分類	BZ3	

器具効率	53%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	53%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	3.3	2.7	2.3	2.1	3.2	2.7	2.3	2.1	3.1	2.6	2.3	2.1	3.0	2.6	2.3	2.1	2.0
	中	0.6	0.8	3.8	3.3	2.9	2.7	3.7	3.3	2.9	2.7	3.6	3.2	2.9	2.7	3.5	3.1	2.9	2.6	2.5
	否	0.56	1.0	4.2	3.7	3.4	3.1	4.1	3.7	3.3	3.1	4.0	3.6	3.3	3.1	3.8	3.5	3.3	3.0	2.9
			1.25	4.5	4.0	3.7	3.5	4.4	4.0	3.7	3.5	4.2	3.9	3.7	3.4	4.1	3.8	3.6	3.4	3.3
下方投影面積		cm <sup>2</sup>	1.5	4.7	4.3	4.0	3.8	4.6	4.2	4.0	3.7	4.4	4.1	3.9	3.7	4.3	4.1	3.8	3.7	3.6
等価発光面積		cm <sup>2</sup>	2.0	4.9	4.6	4.4	4.1	4.8	4.6	4.3	4.1	4.7	4.5	4.3	4.1	4.6	4.4	4.2	4.0	3.9
取付高さ	器具間隔最大限		2.5	5.1	4.8	4.6	4.4	5.0	4.8	4.6	4.4	4.9	4.7	4.5	4.3	4.7	4.6	4.4	4.3	4.2
	横方向 (A)	縦方向 (B)	3.0	5.2	4.9	4.8	4.6	5.1	4.9	4.7	4.6	5.0	4.8	4.6	4.5	4.8	4.7	4.6	4.4	4.3
Hm	1.21Hm	1.21Hm	4.0	5.3	5.1	5.0	4.8	5.2	5.1	4.9	4.8	5.1	5.0	4.8	4.7	5.0	4.9	4.8	4.7	4.5
			5.0	5.4	5.2	5.1	5.0	5.3	5.2	5.1	4.9	5.2	5.1	5.0	4.9	5.1	5.0	4.9	4.8	4.7
			7.0	5.5	5.4	5.3	5.2	5.4	5.3	5.2	5.1	5.3	5.2	5.1	5.0	5.1	5.1	5.0	5.0	4.8
			10.0	5.5	5.5	5.4	5.3	5.5	5.4	5.3	5.3	5.3	5.3	5.2	5.2	5.2	5.2	5.1	5.1	4.9

