

# 屋内照明器具特性

品番 (品名)	XF X4 2 0 DE V														
光源	LED3500_85_2380 x1 2380.0 lm														
管理番号	K0192925(0)DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	4%	反射率	床	10%				10%				10%				10%				0%
下方光束	96%		室指数	照明率 ( X0.01) ZCM																
保守率	良 中 否 0.83 0.81 0.77	0.6	56	43	35	30	54	43	35	30	51	41	34	29	49	40	34	29	27	
		0.8	65	54	46	40	64	53	45	40	60	51	44	39	57	49	43	39	36	
		1.0	72	61	53	47	70	60	52	47	66	58	51	46	63	56	50	45	43	
		1.25	78	68	60	54	76	66	59	54	72	64	58	53	69	62	57	52	49	
下方投影面積	c m <sup>2</sup>	1.5	82	73	65	60	80	71	65	59	76	69	63	58	73	66	61	57	54	
		2.0	87	80	73	68	85	78	72	67	82	75	70	66	78	73	69	65	62	
取付高さ	器具間隔最大限		2.5	91	84	78	74	89	83	77	73	85	80	75	71	82	77	73	70	67
	横方向 (A)	縦方向 (B)	3.0	93	87	82	78	91	86	81	77	88	83	79	75	84	80	77	74	70
1.5m	1.97m	2.13m	4.0	97	92	88	84	95	90	86	83	91	87	84	81	88	84	82	79	75
2	2.6	2.67	5.0	99	95	91	88	97	93	90	86	93	90	87	84	90	87	85	82	79
2.5	3.23	3.23	7.0	101	98	95	92	99	96	94	91	96	93	91	89	92	90	88	87	83
3	3.86	3.81	10.0	103	100	98	96	101	99	97	95	98	96	94	92	94	93	91	90	86

