

屋内照明器具特性	
品番 (品名)	XAD1129N
光源	LLD2020NCB1 ×1 460.0 l m
管理番号	K0187671 (1) DR 1
BZ分類	BZ1

器具効率		8 7 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		8 7 %																					
保守率		良 中 否	0 . 6 7	0 . 6	7 6	7 1	6 8	6 6	7 5	7 1	6 8	6 6	7 4	7 0	6 8	6 6	7 3	7 0	6 8	6 6	6 5		
			0 . 6 3	0 . 8	8 0	7 6	7 4	7 2	8 0	7 6	7 3	7 2	7 9	7 5	7 3	7 1	7 8	7 5	7 3	7 1	7 0		
			0 . 5 6	1 . 0	8 3	8 0	7 7	7 5	8 3	7 9	7 7	7 5	8 1	7 8	7 6	7 5	8 0	7 8	7 6	7 4	7 3		
				1 . 2 5	8 5	8 2	8 0	7 8	8 5	8 2	8 0	7 8	8 3	8 1	7 9	7 7	8 2	8 0	7 8	7 7	7 6		
下方投影面積		c m ²		1 . 5	8 7	8 4	8 2	8 0	8 6	8 4	8 2	8 0	8 5	8 2	8 1	7 9	8 3	8 1	8 0	7 9	7 8		
等価発光面積			c m ²	2 . 0	8 9	8 6	8 5	8 3	8 8	8 6	8 4	8 3	8 6	8 5	8 3	8 2	8 5	8 3	8 2	8 1	8 0		
取付 高さ	器具間隔最大限		2 . 5	9 0	8 8	8 6	8 5	8 9	8 7	8 6	8 4	8 7	8 6	8 5	8 4	8 6	8 5	8 4	8 3	8 1			
	横方向 (A)		縦方向 (B)	3 . 0	9 1	8 9	8 7	8 6	9 0	8 8	8 7	8 6	8 8	8 7	8 6	8 5	8 6	8 5	8 4	8 4	8 2		
H m	0 . 4 3 H m	0 . 4 3 H m	4 . 0	9 1	9 0	8 9	8 8	9 1	8 9	8 8	8 7	8 9	8 8	8 7	8 6	8 7	8 6	8 6	8 5	8 3			
			5 . 0	9 2	9 1	9 0	8 9	9 1	9 0	8 9	8 8	8 9	8 8	8 8	8 7	8 8	8 7	8 6	8 6	8 4			
			7 . 0	9 3	9 2	9 1	9 0	9 2	9 1	9 0	9 0	9 0	8 9	8 9	8 8	8 8	8 8	8 7	8 7	8 5			
			1 0 . 0	9 3	9 2	9 2	9 1	9 2	9 2	9 1	9 1	9 0	9 0	8 9	8 9	8 8	8 8	8 8	8 7	8 5			

