

屋内照明器具特性	
品番 (品名)	X E D 1 1 2 1 L
光源	L L D 2 0 2 0 L C T 1 × 1 4 6 0 . 0 l m
管理番号	K 0 1 7 5 9 6 3 (0) D R 1
B Z 分類	B Z 1

器具効率		7 2 %	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
					1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束		0 %	床	照明率 (X 0 . 0 1)																Z C M	
下方光束		7 2 %		室指数																	
保守率		良	0 . 6 3	0 . 6	5 9	5 4	5 2	5 0	5 8	5 4	5 1	4 9	5 7	5 4	5 1	4 9	5 7	5 3	5 1	4 9	4 8
		中	0 . 6	0 . 8	6 3	5 9	5 7	5 5	6 3	5 9	5 6	5 5	6 2	5 8	5 6	5 4	6 1	5 8	5 6	5 4	5 3
		否	0 . 5 6	1 . 0	6 6	6 3	6 0	5 8	6 6	6 2	6 0	5 8	6 4	6 1	5 9	5 8	6 3	6 1	5 9	5 7	5 6
				1 . 2 5	6 9	6 5	6 3	6 1	6 8	6 5	6 3	6 1	6 7	6 4	6 2	6 0	6 5	6 3	6 2	6 0	5 9
下方投影面積		c m ²	1 . 5	7 0	6 7	6 5	6 3	6 9	6 7	6 5	6 3	6 8	6 6	6 4	6 3	6 7	6 5	6 3	6 2	6 1	
等価発光面積			c m ²	2 . 0	7 2	7 0	6 8	6 6	7 1	6 9	6 7	6 6	7 0	6 8	6 7	6 5	6 8	6 7	6 6	6 5	6 3
取付	器具間隔最大限		2 . 5	7 3	7 1	7 0	6 8	7 2	7 1	6 9	6 8	7 1	6 9	6 8	6 7	7 0	6 8	6 7	6 6	6 5	
高さ	横方向 (A)		縦方向 (B)	3 . 0	7 4	7 2	7 1	6 9	7 3	7 2	7 0	6 9	7 2	7 0	6 9	6 8	7 0	6 9	6 8	6 7	6 6
H m	0 . 4 1 H m			0 . 4 1 H m	4 . 0	7 5	7 3	7 2	7 1	7 4	7 3	7 2	7 1	7 2	7 2	7 1	7 0	7 1	7 0	7 0	6 9
			5 . 0	7 5	7 4	7 3	7 2	7 5	7 4	7 3	7 2	7 3	7 2	7 1	7 1	7 2	7 1	7 0	7 0	6 8	
			7 . 0	7 6	7 5	7 4	7 4	7 5	7 4	7 4	7 3	7 4	7 3	7 2	7 2	7 2	7 2	7 1	7 1	6 9	
			1 0 . 0	7 6	7 6	7 5	7 5	7 6	7 5	7 5	7 4	7 4	7 4	7 3	7 3	7 3	7 2	7 2	7 2	7 0	

