

屋内照明器具特性	
品番 (品名)	S L B 8 0 5 1 5
光源	LDA5 L - D - G - E 1 7 / S / Z 4 × 1 4 4 0 . 0 l m
管理番号	K 0 1 3 9 3 1 1 (0) D B 1
B Z 分類	B Z 5 / 0 . 7 / B Z 4

器具効率		6 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束 下方光束		1 9 % 4 1 %	室指数		照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 7	0 . 6	3 2	2 5	2 1	1 7	3 0	2 4	2 0	1 7	2 7	2 2	1 8	1 6	2 4	2 0	1 7	1 5	1 2		
			0 . 6 3	0 . 8	3 8	3 1	2 7	2 4	3 6	3 0	2 6	2 3	3 2	2 7	2 4	2 2	2 9	2 5	2 2	2 0	1 7		
			0 . 5 6	1 . 0	4 2	3 6	3 2	2 9	4 0	3 4	3 1	2 8	3 6	3 1	2 8	2 6	3 2	2 9	2 6	2 4	2 1		
				1 . 2 5	4 5	4 0	3 6	3 3	4 3	3 8	3 5	3 2	3 9	3 5	3 2	3 0	3 5	3 2	2 9	2 8	2 4		
下方投影面積		c m ²		1 . 5	4 8	4 3	3 9	3 6	4 5	4 1	3 8	3 5	4 1	3 7	3 5	3 3	3 7	3 4	3 2	3 0	2 6		
等価発光面積			c m ²	2 . 0	5 1	4 7	4 4	4 1	4 8	4 5	4 2	4 0	4 4	4 1	3 9	3 7	3 9	3 7	3 5	3 4	2 9		
取付 高さ	器具間隔最大限			2 . 5	5 3	5 0	4 7	4 4	5 0	4 7	4 5	4 3	4 5	4 3	4 1	3 9	4 1	3 9	3 8	3 6	3 1		
		横方向 (A)		縦方向 (B)		3 . 0	5 4	5 1	4 9	4 7	5 2	4 9	4 7	4 5	4 7	4 5	4 3	4 1	4 2	4 0	3 9	3 8	3 3
H m		1 . 6 2 H m		1 . 7 1 H m		4 . 0	5 6	5 4	5 2	5 0	5 3	5 1	4 9	4 8	4 8	4 7	4 5	4 4	4 3	4 2	4 1	4 0	3 4
						5 . 0	5 7	5 5	5 3	5 2	5 4	5 3	5 1	5 0	4 9	4 8	4 7	4 6	4 4	4 3	4 2	4 2	3 6
						7 . 0	5 8	5 7	5 5	5 4	5 5	5 4	5 3	5 2	5 0	4 9	4 8	4 8	4 5	4 5	4 4	4 3	3 7
						1 0 . 0	5 9	5 8	5 7	5 6	5 6	5 5	5 5	5 4	5 1	5 0	5 0	4 9	4 6	4 6	4 5	4 5	3 8

