

屋内照明器具特性

品番 (品名)	S L B 8 0 5 4 7																		
光源	LED2700_70_310 x1 310.0 l m																		
管理番号	K0151379 (0) DB 1																		
B Z 分類	BZ10 / 4.5 / BZ9																		

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		3 5 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		6 5 %																					
保守率		良	0 . 6 7	0 . 6	4 2	2 8	1 9	1 3	3 8	2 6	1 7	1 1	3 2	2 2	1 5	9	2 7	1 8	1 2	7	3		
		中	0 . 6 3	0 . 8	5 0	3 6	2 6	2 0	4 6	3 3	2 5	1 8	3 9	2 8	2 1	1 5	3 2	2 4	1 7	1 3	7		
		否	0 . 5 6	1 . 0	5 6	4 3	3 3	2 6	5 2	4 0	3 1	2 4	4 4	3 4	2 6	2 0	3 6	2 8	2 2	1 7	1 1		
					1 . 2 5	6 2	4 9	4 0	3 2	5 7	4 6	3 7	3 0	4 9	3 9	3 2	2 6	4 1	3 3	2 7	2 2	1 5	
下方投影面積		c m ²		1 . 5	6 7	5 5	4 5	3 8	6 2	5 1	4 2	3 5	5 3	4 4	3 7	3 1	4 4	3 7	3 1	2 6	1 8		
等価発光面積		c m ²		2 . 0	7 3	6 2	5 4	4 6	6 8	5 8	5 0	4 4	5 8	5 0	4 4	3 8	4 9	4 3	3 8	3 3	2 4		
取付 高さ	器具間隔最大限			2 . 5	7 7	6 8	6 0	5 3	7 2	6 3	5 6	5 0	6 2	5 5	4 9	4 4	5 3	4 8	4 3	3 8	2 9		
	横方向 (A)		縦方向 (B)	3 . 0	8 0	7 2	6 4	5 8	7 5	6 7	6 1	5 5	6 5	5 9	5 3	4 8	5 6	5 1	4 6	4 2	3 2		
H m	0 . 0 0 H m	0 . 2 0 H m	4 . 0	8 4	7 7	7 1	6 5	7 9	7 3	6 7	6 2	6 9	6 4	5 9	5 5	6 0	5 5	5 2	4 8	3 7			
			5 . 0	8 7	8 1	7 5	7 0	8 2	7 6	7 1	6 6	7 2	6 7	6 3	5 9	6 2	5 9	5 5	5 2	4 1			
			7 . 0	9 0	8 5	8 1	7 7	8 5	8 0	7 6	7 3	7 5	7 1	6 8	6 5	6 5	6 3	6 0	5 7	4 6			
			1 0 . 0	9 3	8 9	8 5	8 2	8 8	8 4	8 1	7 8	7 8	7 5	7 2	7 0	6 8	6 6	6 4	6 2	5 0			

