

屋内照明器具特性	
品番 (品名)	XAD1121K
光源	LLD2020CU1 ×1 468.0 lm
管理番号	K0178940 (0) DR1
BZ分類	BZ1

器具効率		86 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束		86 %	室指数	照明率 (X0.01) ZCM																	
下方光束																					
保守率		良 中 否	0.6	73	68	65	63	72	68	65	63	71	67	64	62	70	67	64	62	61	
			0.8	77	73	70	68	77	73	70	68	76	72	69	68	74	71	69	67	66	
			1.0	80	76	74	71	80	76	73	71	78	75	73	71	77	74	72	71	70	
			0.56	1.25	83	79	77	75	82	79	76	74	81	78	76	74	79	77	75	74	72
下方投影面積		c m ²	1.5	84	81	79	77	84	81	79	77	82	80	78	76	81	79	77	76	74	
等価発光面積			c m ²	2.0	87	84	82	80	86	83	81	80	84	82	80	79	82	81	80	78	77
取付 高さ	器具間隔最大限		2.5	88	86	84	82	87	85	83	82	85	84	82	81	84	82	81	80	78	
	横方向 (A)		縦方向 (B)	3.0	89	87	85	84	88	86	84	83	86	85	83	82	84	83	82	81	80
H m	0.36 H m	0.36 H m	4.0	90	88	87	86	89	87	86	85	87	86	85	84	85	84	84	83	81	
			5.0	90	89	88	87	89	88	87	86	87	87	86	85	86	85	84	84	82	
			7.0	91	90	89	88	90	89	88	88	88	87	87	86	86	86	85	85	83	
			10.0	91	91	90	90	90	90	89	89	89	88	88	87	87	86	86	86	83	

