

屋内照明器具特性	
品番 (品名)	XAD1402
光源	LLD2000CU1 ×1 566.0 lm
管理番号	K0178773 (0) DR1
BZ分類	BZ5

器具効率		87 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
				室指数	照明率 (X0.01)																Z	CM	
保守率		良 中 否	0.67	0.6	50	39	33	28	49	39	32	28	47	38	32	28	45	37	32	28	26		
			0.63	0.8	59	49	42	37	58	48	42	37	55	47	41	37	53	46	41	37	35		
			0.56	1.0	65	55	49	44	63	55	48	44	61	53	48	43	58	52	47	43	41		
				1.25	70	61	55	50	68	61	55	50	66	59	54	50	63	58	53	49	47		
下方投影面積 等価発光面積		cm ² cm ²		1.5	73	66	60	55	72	65	59	55	69	63	58	54	67	62	57	54	52		
				2.0	78	72	67	63	77	71	66	62	74	69	65	61	72	68	64	61	59		
				2.5	81	76	71	68	80	75	71	67	77	73	69	66	75	71	68	65	63		
				3.0	84	79	75	71	82	78	74	71	80	76	73	70	77	74	71	69	67		
H	m	1.25 H	m	1.25 H	m	4.0	86	83	79	76	85	82	78	76	82	80	77	75	80	78	76	73	71
						5.0	88	85	82	80	87	84	81	79	84	82	80	78	82	80	78	76	74
						7.0	90	88	85	83	89	87	85	83	86	85	83	81	84	83	81	80	77
						10.0	91	90	88	87	90	89	87	86	88	87	85	84	86	85	84	83	80

