

屋内照明器具特性

品番 (品名)	XED3 1 2 0 L	
光源	LLD3 0 2 0 LCT1 × 1	795.0 l m
管理番号	K0190491 (0) DR 1	
B Z 分類	B Z 1	

器具効率	78 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束		0 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	78 %	床	10 %				10 %				10 %				10 %				0 %	
室指数			照明率 (X 0.01)																Z C M	
保守率	良	0.63	0.6	64	59	56	54	63	59	56	53	62	58	55	53	61	58	55	53	52
	中	0.6	0.6	69	64	61	59	68	64	61	59	67	63	61	59	66	63	60	59	58
	否	0.56	1.0	72	68	65	63	71	67	65	63	70	67	64	62	69	66	64	62	61
下方投影面積	等価発光面積	c m ²	1.25	74	71	68	66	74	70	68	66	72	69	67	65	71	68	67	65	64
			1.5	76	73	70	68	75	72	70	68	74	71	69	68	72	70	69	67	66
取付高さ	器具間隔最大限		2.0	78	75	73	72	77	75	73	71	76	74	72	71	74	73	71	70	69
	横方向 (A)	縦方向 (B)	2.5	79	77	75	74	78	76	75	73	77	75	74	72	75	74	73	72	70
H m	0.41 H m	0.41 H m	3.0	80	78	77	75	79	78	76	75	78	76	75	74	76	75	74	73	71
			4.0	81	80	78	77	80	79	78	77	79	77	76	75	77	76	75	74	73
			5.0	82	81	79	78	81	80	79	78	79	78	77	77	78	77	76	75	74
			7.0	82	82	81	80	82	81	80	79	80	79	78	78	78	78	77	77	75
			10.0	83	82	82	81	82	81	81	80	80	80	79	79	79	78	78	77	75

