

屋内照明器具特性

品番 (品名)	XF X4 2 5 FE V															
光源	LED3500_85_1960 x1 1960.0 1 m															
管理番号	K0192929 (0) DB 1															
BZ分類	BZ4 / 0.7 / BZ3 / 3.5 / BZ4															

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	0 %	室指数	照明率 (X0.01)																ZCM		
下方光束	100 %																				
保守率	良 中 否	0.81	0.6	62	50	43	38	60	50	43	38	58	49	43	38	56	48	42	38	36	
		0.77	0.8	72	61	54	49	70	61	54	49	68	59	53	49	66	58	53	49	47	
			1.0	78	69	62	57	77	68	62	57	74	67	61	56	72	65	60	56	54	
		0.68	1.25	84	75	69	64	82	75	69	64	80	73	68	63	77	71	67	63	61	
下方投影面積	c m ²	1.5	87	80	74	69	86	79	74	69	83	77	72	68	81	76	71	68	66		
		2.0	92	86	81	77	91	85	81	77	88	83	79	76	86	82	78	75	73		
取付高さ	器具間隔最大限		2.5	96	90	86	82	94	89	85	81	91	87	84	81	89	85	82	80	77	
	横方向 (A)	縦方向 (B)	3.0	98	93	89	86	96	92	88	85	94	90	87	84	91	88	85	83	80	
1.5m	1.97 m	2.02 m	4.0	100	97	93	91	99	96	93	90	96	93	91	89	94	91	89	87	85	
2	2.6	2.53	5.0	102	99	96	94	101	98	95	93	98	96	94	92	96	94	92	90	88	
2.5	3.24	3.05	7.0	104	102	99	98	102	100	99	97	100	98	97	95	98	96	95	94	91	
3	3.87	3.59	10.0	105	104	102	101	104	102	101	100	101	100	99	98	99	98	97	96	93	

