

| | |
|----------|------------------------------|
| 屋内照明器具特性 | |
| 品番 (品名) | XF X4 2 6 F E V |
| 光源 | LED3500_85_1530 x1 1530.0 lm |
| 管理番号 | K0192934 (0) DB 1 |
| BZ分類 | BZ4 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|------------------|---------|--------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|----|----|----|-----|----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| 上方光束 | 0% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 下方光束 | 100% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 中 否 | 0.77 | 0.6 | 60 | 49 | 42 | 37 | 59 | 48 | 41 | 37 | 57 | 47 | 41 | 36 | 55 | 46 | 41 | 36 | 34 |
| | | 0.72 | 0.8 | 70 | 60 | 52 | 47 | 69 | 59 | 52 | 47 | 66 | 58 | 51 | 47 | 64 | 56 | 51 | 47 | 45 |
| | | 0.68 | 1.0 | 77 | 67 | 60 | 55 | 75 | 66 | 60 | 55 | 73 | 65 | 59 | 54 | 70 | 63 | 58 | 54 | 52 |
| | | | 1.25 | 82 | 74 | 67 | 62 | 81 | 73 | 67 | 62 | 78 | 71 | 66 | 61 | 76 | 70 | 65 | 61 | 59 |
| 下方投影面積 | c m ² | 1.5 | 86 | 78 | 72 | 67 | 85 | 77 | 72 | 67 | 82 | 76 | 71 | 66 | 79 | 74 | 70 | 66 | 64 | |
| | | 2.0 | 92 | 85 | 80 | 75 | 90 | 84 | 79 | 75 | 87 | 82 | 78 | 74 | 85 | 80 | 76 | 73 | 71 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 95 | 89 | 84 | 80 | 93 | 88 | 84 | 80 | 90 | 86 | 82 | 79 | 88 | 84 | 81 | 78 | 76 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 97 | 92 | 88 | 84 | 96 | 91 | 87 | 84 | 93 | 89 | 86 | 83 | 90 | 87 | 84 | 82 | 79 |
| 1.5m | 1.71m | 2.05m | 4.0 | 100 | 96 | 93 | 90 | 98 | 95 | 92 | 89 | 96 | 93 | 90 | 88 | 93 | 91 | 88 | 86 | 84 |
| 2 | 2.26 | 2.57 | 5.0 | 101 | 98 | 96 | 93 | 100 | 97 | 95 | 92 | 97 | 95 | 93 | 91 | 95 | 93 | 91 | 89 | 87 |
| 2.5 | 2.81 | 3.12 | 7.0 | 103 | 101 | 99 | 97 | 102 | 100 | 98 | 96 | 100 | 98 | 96 | 94 | 97 | 96 | 94 | 93 | 90 |
| 3 | 3.36 | 3.67 | 10.0 | 105 | 103 | 102 | 100 | 104 | 102 | 101 | 99 | 101 | 100 | 99 | 97 | 99 | 98 | 97 | 96 | 93 |

