

屋内照明器具特性

品番 (品名)	NYY75063 + NYY90150
光源	LED3000_70_580 x1 580.0 l m
管理番号	K0152450 (*) DJ 1
B Z 分類	BZ1

器具効率		1 0 2 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良	0 . 6 7	0 . 6	1 0 1	9 9	9 7	9 6	1 0 1	9 9	9 7	9 6	1 0 0	9 8	9 7	9 6	1 0 0	9 8	9 7	9 6	9 5
		中	0 . 6 3	0 . 8	1 0 3	1 0 1	9 9	9 8	1 0 3	1 0 1	9 9	9 8	1 0 2	1 0 0	9 9	9 8	1 0 1	9 9	9 8	9 7	9 7
		否	0 . 5 6	1 . 0	1 0 4	1 0 2	1 0 1	1 0 0	1 0 4	1 0 2	1 0 0	9 9	1 0 3	1 0 1	1 0 0	9 9	1 0 2	1 0 0	9 9	9 9	9 8
下方投影面積 等価発光面積		c m ²	1 . 2 5	1 0 5	1 0 3	1 0 2	1 0 1	1 0 5	1 0 3	1 0 2	1 0 1	1 0 4	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 8
			1 . 5	1 0 6	1 0 4	1 0 3	1 0 2	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 3	1 0 2	1 0 1	1 0 3	1 0 2	1 0 1	1 0 0	9 9	
取付 高さ		器具間隔最大限	2 . 0	1 0 7	1 0 6	1 0 4	1 0 3	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 1	1 0 0	
			2 . 5	1 0 8	1 0 6	1 0 5	1 0 4	1 0 7	1 0 6	1 0 5	1 0 4	1 0 5	1 0 4	1 0 3	1 0 3	1 0 2	1 0 1	1 0 1	1 0 0		
H _m		0 . 2 8 H _m	0 . 2 8 H _m	3 . 0	1 0 8	1 0 7	1 0 6	1 0 5	1 0 7	1 0 6	1 0 5	1 0 4	1 0 5	1 0 5	1 0 4	1 0 3	1 0 4	1 0 3	1 0 3	1 0 2	1 0 0
				4 . 0	1 0 9	1 0 8	1 0 7	1 0 6	1 0 8	1 0 7	1 0 6	1 0 5	1 0 6	1 0 5	1 0 4	1 0 4	1 0 4	1 0 3	1 0 3	1 0 3	1 0 2
				5 . 0	1 0 9	1 0 8	1 0 7	1 0 7	1 0 8	1 0 7	1 0 7	1 0 6	1 0 6	1 0 5	1 0 5	1 0 4	1 0 4	1 0 4	1 0 3	1 0 1	
				7 . 0	1 0 9	1 0 9	1 0 8	1 0 8	1 0 8	1 0 8	1 0 7	1 0 7	1 0 6	1 0 6	1 0 5	1 0 5	1 0 4	1 0 4	1 0 4	1 0 1	
				1 0 . 0	1 1 0	1 0 9	1 0 9	1 0 8	1 0 8	1 0 8	1 0 8	1 0 7	1 0 6	1 0 6	1 0 6	1 0 6	1 0 4	1 0 4	1 0 4	1 0 1	

