

屋内照明器具特性	
品番 (品名)	XF X4 2 9 NEL
光源	LED3000_85_2300 x1 2300.0 1 m
管理番号	K0192447 ( 0 ) DR 1
BZ分類	BZ5

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %																																							
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																							
		床	10 %				10 %				10 %				10 %				0 %																																							
上方光束	4 %	室指数																			照明率 ( X0.01 )																			ZCM																		
下方光束	96 %																																																									
保守率	良 中 否	0.83	0.6	5.5	4.3	3.5	3.0	5.4	4.2	3.5	3.0	5.1	4.1	3.4	2.9	4.9	4.0	3.3	2.9	2.7																																						
		0.81	0.8	6.5	5.4	4.6	4.0	6.3	5.3	4.5	3.9	6.0	5.1	4.4	3.9	5.7	4.9	4.3	3.8	3.6																																						
		0.77	1.0	7.2	6.1	5.3	4.7	7.0	6.0	5.2	4.7	6.6	5.8	5.1	4.6	6.3	5.6	5.0	4.5	4.2																																						
			1.25	7.8	6.8	6.0	5.4	7.6	6.6	5.9	5.4	7.2	6.4	5.8	5.3	6.8	6.2	5.6	5.2	4.9																																						
下方投影面積		c m <sup>2</sup>																																																								
等価発光面積		c m <sup>2</sup>																																																								
取付高さ	器具間隔最大限																																																									
	横方向 (A)	縦方向 (B)																																																								
1.5m	1.96 m	2.1 m	4.0	9.6	9.2	8.7	8.4	9.4	9.0	8.6	8.3	9.1	8.7	8.4	8.1	8.7	8.4	8.1	7.9	7.5																																						
2	2.58	2.64	5.0	9.8	9.4	9.1	8.7	9.7	9.3	8.9	8.6	9.3	9.0	8.7	8.4	8.9	8.7	8.4	8.2	7.8																																						
2.5	3.21	3.2	7.0	10.1	9.8	9.5	9.2	9.9	9.6	9.3	9.1	9.5	9.3	9.1	8.9	9.2	9.0	8.8	8.6	8.2																																						
3	3.84	3.77	10.0	10.3	10.0	9.8	9.6	10.1	9.9	9.7	9.5	9.7	9.6	9.4	9.2	9.4	9.2	9.1	9.0	8.6																																						

