

屋内照明器具特性	
品番 (品名)	XAD1403
光源	LLD2000CU1 ×1 566.0 lm
管理番号	K0178775 (0) DR1
BZ分類	BZ5

器具効率		84 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z CM
保守率		良 中 否	0.67	0.6	48	38	31	27	47	37	31	27	45	36	31	27	43	36	30	26	25
			0.63	0.8	56	47	40	36	55	46	40	35	53	45	39	35	51	44	39	35	33
			0.56	1.0	62	53	47	42	61	52	46	42	58	51	46	41	56	50	45	41	39
				1.25	67	59	53	48	66	58	52	48	63	57	52	48	61	55	51	47	45
下方投影面積		cm ²	1.5	70	63	57	53	69	62	57	53	67	61	56	52	64	59	55	52	50	
			2.0	75	69	64	60	74	68	64	60	71	66	62	59	69	65	61	58	56	
等価発光面積		cm ²	2.5	78	73	69	65	77	72	68	64	74	70	67	64	72	68	65	63	61	
			3.0	80	76	72	68	79	75	71	68	76	73	70	67	74	71	68	66	64	
H m	1.25 H m	1.25 H m	4.0	83	79	76	73	82	78	75	73	79	76	74	72	77	75	72	70	68	
			5.0	84	81	79	76	83	80	78	76	81	79	76	74	79	77	75	73	71	
			7.0	86	84	82	80	85	83	81	79	83	81	79	78	81	79	78	77	74	
			10.0	88	86	84	83	86	85	84	82	84	83	82	81	82	81	80	79	77	

