

屋内照明器具特性

品番 (品名)	XFL312VEZ	
光源	LDL40S.N/14/26(2600A) ×1 2600.0 1m	
管理番号	K0126504(1)DB1	
BZ分類	BZ3/0.7/BZ2	

器具効率	64%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	0%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	64%																																																						
保守率	良 0.81 中 0.77 否 0.68	0.6	41	35	30	28	41	34	30	27	39	34	30	27	38	33	30	27	26																																				
		0.8	48	42	38	35	47	42	38	35	46	41	38	35	45	40	37	35	34																																				
		1.0	52	47	43	40	52	47	43	40	50	46	43	40	49	45	42	40	39																																				
		1.25	56	51	48	45	55	51	47	45	53	50	47	45	52	49	46	44	43																																				
下方投影面積	c m ²	1.5	58	54	51	48	57	53	50	48	56	52	50	48	54	51	49	47	46																																				
		2.0	61	58	55	53	60	57	54	52	58	56	54	52	57	55	53	51	50																																				
取付高さ	器具間隔最大限		2.5	63	60	57	55	62	59	57	55	60	58	56	54	59	57	55	54	52																																			
	横方向 (A)	縦方向 (B)	3.0	64	61	59	57	63	61	59	57	61	59	58	56	60	58	57	56	54																																			
1.5m	1.93m	1.99m	4.0	65	63	62	60	64	63	61	60	63	61	60	59	61	60	59	58	56																																			
2	2.56	2.49	5.0	66	64	63	62	65	64	62	61	64	62	61	60	62	61	60	59	58																																			
2.5	3.18	3.01	7.0	67	66	65	64	66	65	64	63	65	64	63	62	63	62	62	61	59																																			
3	3.79	3.54	10.0	68	67	66	65	67	66	65	65	65	65	64	64	64	63	63	62	61																																			

