

屋内照明器具特性	
品番 (品名)	XAD3 1 2 0 K
光源	LLD3020CU1 ×1 615.0 l m
管理番号	K0178934 (0) DR 1
B Z 分類	BZ1

器具効率		93 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束		93 %																						
保守率		良	0.67	0.6	77	72	68	65	77	71	68	65	75	71	68	65	74	70	67	65	64			
		中	0.63	0.8	83	78	74	71	82	77	74	71	80	76	73	71	79	76	73	71	70			
		否	0.56	1.0	86	81	78	76	85	81	78	75	84	80	77	75	82	79	77	75	74			
				1.25	89	85	82	79	88	84	81	79	86	83	81	79	85	82	80	78	77			
下方投影面積		c m ²		1.5	91	87	84	82	90	87	84	82	88	85	83	81	87	84	82	81	79			
等価発光面積		c m ²		2.0	93	90	88	86	92	90	87	85	90	88	86	85	89	87	85	84	82			
取付 高さ	器具間隔最大限			2.5	95	92	90	88	94	91	89	88	92	90	88	87	90	88	87	86	84			
	横方向 (A)		縦方向 (B)	3.0	96	93	92	90	95	93	91	89	93	91	90	88	91	90	88	87	85			
H m	0.34 H m		0.34 H m	4.0	97	95	94	92	96	94	93	92	94	93	91	90	92	91	90	89	87			
				5.0	98	96	95	94	97	95	94	93	95	93	93	92	93	92	91	90	88			
				7.0	98	97	96	96	97	96	96	95	95	95	94	93	93	93	92	92	89			
				10.0	99	98	98	97	98	97	97	96	96	95	95	94	94	93	93	93	90			

