

# 屋内照明器具特性

品番 (品名)	XED3 1 2 1 L	
光源	LLD3 0 2 0 LCT1 × 1	795.0 l m
管理番号	K0190488 ( 0 ) DR 1	
B Z 分類	B Z 1	

器具効率	68 %	天井	80 %				70 %				50 %				30 %				0 %				
	上方光束		0 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
下方光束	68 %	床	10 %				10 %				10 %				10 %				0 %				
室指数	照明率 ( X 0.01 )																			Z C M			
保守率	良	0.63	0.6	0.6	5.6	5.1	4.9	4.7	5.5	5.1	4.8	4.7	5.4	5.1	4.8	4.6	5.3	5.0	4.8	4.6	4.6		
	中	0.6	0.6	0.6	6.0	5.6	5.3	5.1	5.9	5.6	5.3	5.1	5.8	5.5	5.3	5.1	5.7	5.5	5.3	5.1	5.0		
	否	0.56	0.56	0.56	6.3	5.9	5.6	5.5	6.2	5.9	5.6	5.4	6.1	5.8	5.6	5.4	6.0	5.7	5.5	5.4	5.3		
下方投影面積	等価発光面積	c m <sup>2</sup>	c m <sup>2</sup>	1.25	6.5	6.2	5.9	5.7	6.4	6.1	5.9	5.7	6.3	6.0	5.8	5.7	6.2	6.0	5.8	5.7	5.6		
				1.5	6.6	6.3	6.1	6.0	6.5	6.3	6.1	5.9	6.4	6.2	6.0	5.9	6.3	6.1	6.0	5.8	5.7	5.7	
取付高さ	器具間隔最大限		H m	0.41 H m	H m	0.41 H m	2.5	6.9	6.7	6.6	6.4	6.8	6.7	6.5	6.4	6.7	6.5	6.4	6.3	6.6	6.4	6.3	6.2
	横方向 ( A )	縦方向 ( B )					3.0	7.0	6.8	6.7	6.5	6.9	6.7	6.6	6.5	6.8	6.6	6.5	6.4	6.6	6.5	6.4	6.6
H m	0.41 H m	0.41 H m	4.0	7.1	6.9	6.8	6.7	7.0	6.9	6.8	6.7	6.8	6.7	6.7	6.6	6.7	6.6	6.5	6.5	6.5	6.3		
			5.0	7.1	7.0	6.9	6.8	7.0	6.9	6.9	6.8	6.9	6.8	6.7	6.7	6.8	6.7	6.6	6.6	6.6	6.4		
			7.0	7.2	7.1	7.0	6.9	7.1	7.0	7.0	6.9	6.9	6.9	6.8	6.8	6.8	6.8	6.8	6.8	6.7	6.7	6.5	
10.0	7.2	7.2	7.1	7.0	7.1	7.1	7.0	7.0	7.0	6.9	6.9	6.9	6.8	6.8	6.8	6.8	6.8	6.7	6.6				

